

# MAXIFY GX4060

## MegaTank

---

## TECHNICAL SPECIFICATIONS



**Canon**

# MAXIFY GX4060

## MegaTank



### ENJOY ECONOMICAL HIGH-YIELD PRINTING

Comprising of Canon's new MegaTank ink technology, the MAXIFY GX4060 MegaTank is capable of printing up to 6,000 page in black, and up to 14,000 pages in colour<sup>1</sup>, reducing the chances that you will run out of ink when you need it most. Canon's Economy printing mode will also enable you to decrease printing costs and maximise your productivity even further by reducing the consumption of ink, achieving yields of up to 9,000 in black, and up to 21,000 in colour.



### SUPER CHARGED PRODUCTIVITY

The MAXIFY GX4060 MegaTank has a large paper capacity. The Front Cassette holds 250 sheets of plain paper while the Rear Tray can handle 100 sheets of plain paper. Collectively this printer has a capacity of 350 sheets – you will spend less time refilling your printer.



### GET THE BENEFIT OF EASY MAINTENANCE

The MAXIFY GX4060 MegaTank offers the benefit of a user replaceable Print head, Maintenance Cartridge and a Paper Roller which can be easily cleaned. With the convenience of being able to easily maintain it yourself, it means less downtime with printing.



### ALL-IN-ONE PRINTING FOR YOUR BUSINESS MEDIA NEEDS

In addition to delivery high-quality documents, MAXIFY MegaTank printers offer compatibility with a wide range of media types and sizes. With the MAXIFY GX4060 MegaTank you can now also print thick, rigid paper up to 0.7mm thick such as posterboard. Now create personalised posters for your business easily.



<sup>1</sup>Approx. yields are based on Canon original method using test patterns ISO/IEC 24712 (Colour chart). The estimated page yields are determined not based on the initial set of bundled ink bottles, but based on subsequent sets of ink bottles after print head nozzles have been filled with ink from the initial set of ink bottles. Black and colour page yields are not to be combined. Page yields varies significantly depending on contents printed and other factors.

<sup>2</sup>Economy mode plain paper Page Yield is an estimate.

<sup>3</sup>AirPrint and Mopria are available for download via the Apple Store (iOS) and Play Store (Android).

### What inks can I use with my printer?

- GI-66BK
- GI-66C
- GI-66M
- GI-66Y



# MAXIFY GX4060



## SPECIFICATIONS

| GENERAL FEATURES   |  |
|--|--|
| Model  | MAXIFY GX4060 MegaTank   |
| Ink Type   | 4 Bottles (PGBK / C / M / Y)                                       |
| Maximum Print Resolution                                 | 600 dpi*1 x 1,200 dpi  |
| Size   | Approx. 399 x 417 x 251mm<br>Approx. 15.8 x 16.4 x 9.9 inch        |
| Weight   | Approx. 9.5 kg<br>Approx. 20.9 lbs                                 |
| Display  | 2.7" / 6.7 cm LCD (Monochrome)                                     |
| Interface  | USB / Wireless   |
| Input Power  | AC 100-240 V, 50 / 60 Hz   |
| PRINT SPEED  |  |
| Document: Colour*2                                       | Approx. 13.0 ipm   |
| Document: Black & White*2                                | Approx. 18.0 ipm   |
| POWER CONSUMPTION  |  |
| OFF  | Approx. 0.1 W  |
| Standby (MFP: scanning lamp is off) USB connection to PC | Approx. 0.9 W  |
| Standby (all ports connected, MFP: scanning lamp is off) | Approx. 1.4 W  |
| Time to enter Standby mode                               | Approx. 5 min  |
| ENVIRONMENT  |  |
| Operating Environment*5                                  | Temperature: 5 - 35 °C Humidity: 10 - 90 %RH (no dew condensation) |
| Recommended Environment *6                               | Temperature: 15 -30 °C Humidity: 10 - 80 %RH (no dew condensation) |
| Storage Environment                                      | Temperature: 0 - 40 °C Humidity: 5 - 95 %RH (no dew condensation)  |
| ACOUSTIC NOISE (PC PRINT)                                |  |
| Quiet Mode   | Available  |
| Acoustic Noise (PC print) Plain Paper*7                  | Approx. 49.0 dB(A)   |
| PRINT HEAD / INK   |  |
| Number of Nozzles  | Total 4,352 nozzles (BK: 1,280 nozzles, C/M/Y 1,024 nozzles)       |
| Compatible Inks  | GI-66BK, GI-66C, GI-66Y, GI-66M                                    |
| PRINTABLE WIDTH  |  |
|  | Up to 206 mm (8 inch)  |

### PRINTABLE AREA

|                          |  |
|--------------------------|--|
| <b>Bordered Printing</b> | <ul style="list-style-type: none"> <li>#10 Envelope, DL Envelope, Envelope C5, Monarch Envelope</li> <li>Top: 12.7 mm, Bottom: 12.7 mm, Right: 5.6 mm, Left: 5.6 mm</li> <li>4" x 6", 5" x 7", 7" x 10", 8" x 10"</li> <li>Top: 3 mm, Bottom: 5 mm, Right: 3.4 mm, Left: 3.4 mm</li> <li>Square(127 mm x 127 mm)</li> <li>Top: 6 mm, Bottom: 6 mm, Right: 6 mm, Left: 6 mm</li> <li>Other</li> <li>Top: 5 mm, Bottom: 5 mm, Right: 5 mm, Left: 5 mm</li> <li>Bordered Auto 2-sided printing</li> <li>Top: 5 mm, Bottom: 5 mm, Right: 5 mm, Left: 5 mm</li> </ul> |
|--------------------------|--|

### SUPPORT MEDIA

|                       |  |
|-----------------------|--|
| <b>Rear Tray</b>      | Plain Paper (64 g/m2 - 105 g/m2), High Resolution Paper (HR-101N), Photo Paper Plus Glossy II (PP-301), Photo Paper Pro Luster (LU-101), Photo Paper Plus Semi-gloss (SG-201), Photo Paper Glossy (GP-701), Matte Photo Paper (MP-101), Envelope, Magnetic Photo Paper(MG-101), Restickable Photo Paper(RP-101), Light Fabric Iron on Transfers(LF-101), Double sided Matte Paper(MP-101D) |
| <b>Cassette</b>       | Plain Paper (64 g/m2 - 105 g/m2)   |
| <b>Rear Flat Tray</b> | Paperboard   |

### PAPER SIZE

|                       |  |
|-----------------------|--|
| <b>Rear Tray</b>      | A4, A5, A6, B5, LTR, LGL, B-Oficio, M-Oficio, Foolscap, FS, Executive, #10 Envelope, DL Envelope, C5 Envelope, Monarch Envelope, Card Size (91 mm x 55 mm), 4" x 6", 5" x 7", 7" x 10", 8" x 10", Square (127 mm x 127 mm), Custom size (width: 89 mm - 216 mm, length: 127 mm - 1,200 mm) |
| <b>Cassette</b>       | A4, A5, B5, LTR, Executive [Custom size] width 148 mm - 215.9 mm, length 210 mm - 297 mm   |
| <b>Rear Flat Tray</b> | A4, B5, LTR [Custom size] width 89 mm - 215.9 mm, length 127 mm - 1,200 mm   |

### PAPER HANDLING (MAXIMUM NUMBER)

|                             |  |
|-----------------------------|--|
| <b>Rear Tray</b>            | Plain Paper (64 g/m2): 100, High Resolution Paper (HR-101N): 80. 4" x 6" - Photo Paper Plus Glossy II (PP-301), Photo Paper Plus Semi-gloss (SG-201), Photo Paper Glossy (GP-701): 20. Matte Photo Paper (MP-101), Magnetic Photo Paper(MG-101), Restickable Photo Paper(RP-101): 1. 5" x 7" - Photo Paper Plus Glossy II (PP-301), Photo Paper Plus Semi-gloss (SG-201): 10 |
| <b>Cassette</b>             | Plain Paper (64 g/m2): 250   |
| <b>Auto Document Feeder</b> | Plain Paper (64 g/m2): 35 LGL: 5, others: 1  |
| <b>Rear Flat Tray</b>       | 1  |

### PAPER WEIGHT

|                       |   |
|-----------------------|---|
| <b>Rear Tray</b>      | Plain Paper: 64 g/m2 -105 g/m2, Canon paper: max paper weight : approx. 265 g/m2, Photo Paper Plus Glossy II (PP-301) |
| <b>Cassette</b>       | Plain Paper: 64 g/m2 -105 g/m2  |
| <b>Rear Flat Tray</b> | Paper Thickness : 0.1 mm to 0.7 mm  |

# MAXIFY GX4060



## SPECIFICATIONS

### SCANNER FUNCTIONS

|                                   |  |
|-----------------------------------|--|
| Scanner Type                      | Flatbed (ADF / Platen)                                       |
| Optical Resolution*4              | 1,200 x 2,400 dpi  |
| Scanning Bit Depth (Input/Output) | Grayscale: 16 bit / 8 bit<br>Colour: RGB each 16 bit / 8 bit |
| Maximum Document Size             | A4 / LTR (216 x 297 mm)                                      |

### COPY FUNCTIONS

|                       |  |
|-----------------------|--|
| Maximum Document Size | A4 / LTR   |
| Compatible Media      | Plain Paper (64 g/m2 - 105 g/m2), Photo Paper Plus Glossy II (PP-301), Photo Paper Pro Luster (LU-101), Photo Paper Plus Semi-gloss (SG-201), Photo Paper Glossy (GP-701), Matte Photo Paper (MP-101), Light Fabric Iron on Transfers (LF-101) |
| Image Quality         | 3 positions (Economy, Standard, High)  |
| Multiple Copy         | Black & White / Colour: max. 99 pages  |

### FAX

|                    |  |
|--------------------|--|
| Applicable Line    | PSTN   |
| Transmission Speed | Black: Approx. 3 sec<br>Colour: Approx. 1 min  |
| Fax Resolution     | Black: Standard - 8pels/mm x 3.85 lines/mm. Fine - 8pels/mm x 7.7 lines/mm. Extra Fine - 300 dpi x 300 dpi.<br>Colour: 200 dpi x 200 dpi |
| Print Size         | A4, LTR, LGL   |
| Scanning Width     | A4, LTR  |
| Modern Speed       | Maximum 33.6 kbps (Automatic fall back)  |

### PRINTING SOLUTION

|                             |  |
|-----------------------------|--|
| Available for               | AirPrint / Mopria / Canon Print Service (for Android) / PIXMA Cloud Link / Canon PRINT Inkjet/SELPHY (for iOS / Android) / Camera Direct |
| Minimum System Requirements | Windows <sup>R</sup> 11, 10, 8.1, 7SP1. Windows Server 2022/2019/2016/2012 R2/2008 R2 SP1. macOS 10.14.6~12                              |

### What's in the Box?

- Printer
- Power Cord
- Full set of Starter Ink bottles
- Getting started guide

### Contents



USB cable not included.

# MAXIFY GX4060



## DISCLAIMERS

- \*1: Ink droplets can be placed with a pitch of 1/4800 inch at minimum.
- \*2: Document print speeds are the averages of ESAT (Estimated Saturated Throughput) (Word, Excel, PDF) in Office Category Test for the default simplex mode, ISO/IEC 24734. Photo print speed is based on the default setting using ISO/JIS-SCID N2 on Photo Paper Plus Glossy II and does not take into account data processing time on host computer. Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.
- \*3: Paper types NOT supported for borderless printing are as follows: Envelope, High Resolution Paper, T-Shirt Transfer, Photo Stickers
- \*4: Optical resolution is a measure of maximum hardware sampling resolution, based on ISO 14473 standard.
- \*5: The performance of the printer may be reduced under certain temperature and humidity conditions.
- \*6: For the temperature and humidity conditions of papers such as photo paper, refer to the paper's packaging or the supplied instructions
- \*7: Acoustic Noise is measured based on ISO7779 standard with default setting.

### Standard disclaimers:

- If your inkjet printer is found defective within the applicable manufacturer warranty period (1 Year), we'll replace it with the same, or an equivalent model. Excludes damage caused by external factors. Canon's full replacement promise is in addition to your rights under Australian Consumer Law which, depending on the type of fault, includes repair, replacement or a refund. For full terms see: [www.canon.com.au/printassist](http://www.canon.com.au/printassist) or the card in the printer box. Only for products purchased at Authorised Canon Australia retailers
- Photo print speed is based on the default setting using ISO/JIS-SCID N2 on Photo Paper Plus Glossy II and does not take into account data processing time on host computer. Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.
- Page yield of ink bottle used for initial setup is lower than a replacement as a certain amount of ink is used to fill the printhead during setup. Page yield is the estimated value based on Canon's individual test method using the ISO/IEC 24712 colour chart and continuous printing simulation with the replacement ink bottles after initial setup. Black and colour page yields are not to be combined. Page yield varies significantly depending on contents printed and other factors.
- USB cable not included.

Note: Ink must be available in each ink-tank for all functions including copy, print and scan. Some functions may not work unless an internet connection established.

**Canon**

**[www.canon.com.au](http://www.canon.com.au)  
[www.canon.co.nz](http://www.canon.co.nz)**