

#### **KEY FEATURES**

# Low upkeep

 Enjoy reliable printing with minimal maintenance. The automatic seal removal mechanism makes cartridge replacement effortless.

## Improved organisation

 The Application Library Function allows you to create shortcut icons to help you be more organised when it comes to scanning, copying or using form templates.

#### Reduced power usage

 A Sleep Mode feature minimises electricity consumption and helps reduce your carbon footprint.



# A LIGHTER TOUCH

With an intuitive user interface that allows you to do tasks such as copying and scanning with just a tap of your finger, you're now able to do your work quicker, and with minimal effort.



### MORE CONTROL

With Department ID you can limit print usage and save printing costs — making the MF543x as cost efficient as it is productive.



#### HIGHER PRINT YIELDS

Incredible print yields of up to 21,000 pages means less frequent toner replacements, and more time to focus on your core business.



# **GREATER SPEED**

Capable of print speeds of up to 43 ppm, you can now be confident that your print jobs will be delivered in good time, allowing you to focus on your next project.



#### FLEXIBILITY AND MOBILITY

Print directly from your mobile device, using multiple apps such as Canon PRINT Business, Apple® AirPrint®, Google Cloud Print™, Mopria® and Canon Print Service. Not only do you enjoy greater convenience, you can look forward to improved productivity and all the flexibility you could ask for.



# VERSATILE PRINTING OPTIONS

The ability to print on small media such as A5 or even A6 provides added versatility, and is perfect for invoices, flyers, or simply to reduce the size of prints you couldn't before.



#### IMPROVED CONNECTIVITY

Not only does the Gigabit Ethernet connection ensure fast data transfers, these versatile printers can be connected to the network via Wi-Fi or directly by cable. Being connected has never been simpler.

# imageCLASS MF543x SPECIFICATIONS

Print	
Printing Method	Monochrome Laser Beam Printing
Print Speed	Single sided: Up to 43 ppm (A4) Double sided: Up to 34.4 ipm (A4)
Print Resolution (Max.)	600 × 600 dpi
Print Quality with Image	Up to 1200 × 1200 dpi
Refinement Technology Warm-up Time	14 sec or less
(from Power On)	A 57 1
First Printout Time (FPOT)	Approx. 5.7 sec or less
Recovery Time (from Sleep Mode)	4.0 sec or less
Print Language	UFRII, PCL 5e, PCL6, Adobe® PostScript
Auto Duplex Print	Standard
Available Paper Size for Auto Duplex Print	A4, Legal, Letter, Foolscap, Indian Legal
USB Direct Print	Supported File Format: JPEG, TIFF, PDF
Print Margins	5 mm – top, bottom, left and right (Envelope: 10 mm)
Print Features	Poster, Booklet, Watermark, Page Composer, Toner Saver
Advanced Printing Features	Secure Print; Print from USB memory key (JPEG/TIFF/PDF); Barcode Print; Touch & Print (NFC); Google Cloud Print Ready; iOS: AirPrint, Canon PRINT Business app; Android; Mopria certified, Canon PRINT Business app, Canon Print Service Plug-in
Сору	
Copy Speed	Single sided (A4): Up to 43 ppm Double sided (A4): Up to 34.4 ppm
Copy Resolution	600 × 600 dpi
First Copy Time (FCOT)	ADF (A4): Approx. 6.4 sec or less; Platen (A4): Approx. 6.3 sec or less
Maximum Number of Copies	Up to 999 copies
Reduce/Enlargement	25–400% in 1% increments
Copy Features	Frame Erase, Collate, 2 on 1, 4 on 1, ID card copy
Scan	B 1 1 2 1 1 1 200 200 1 1
Scan Resolution	Laser Resolution: Up to 600 × 600 dpi Smoothing Resolution: 1200 × 1200 dpi
Scan Type	Colour Contact Image Sensor
Maximum Scan Size	Platen Glass: Up to 215.9 × 355.6 mm Feeder: Up to 215.9 × 355.6 mm
Scan Speed	Single sided mono: 38 ipm (300 × 600 dpi) Single sided colour: 13 ipm (300 × 600 dpi) Double sided mono: 70 ipm (300 × 600 dpi) Double sided colour: 26 ipm (300 × 600 dpi)
Colour Depth	24-bit
Pull Scan	Yes, USB and Network
Push Scan (Scan to PC) with MF Scan Utility	Yes, USB and Network
Scan to USB (via USB Host 2.0)	Yes
Scan to Cloud	Through MF Scan Utility, TIFF/JPEG/PDF/PNG
Scan Driver Compatibility	TWAIN, WIA
Scan to E-Mail	TIFF/JPEG/PDF/Compact PDF/Searchable PDF/ Encrypted PDF3/ PDF (Digital signature)
Send	CMD F I ETD 'FAVC'
Send Method	SMB, Email, FTP, iFAX Simple
Colour Mode Scan Resolution	Full Colour, Grayscale, Monochrome 300 × 600 dpi
File Format	JPEG, TIFF, PDF, Compact PDF, PDF (OCR)
Fax	5. 25, 1,1 D1, Compact D1,1 D1 (OCK)
Modem Speed	Up to 33.6 Kbps
Fax Resolution	Standard: 200 × 100 dpi Fine: 200 × 200 dpi Super fine: 200 × 400 dpi Ultra fine: 400 × 400 dpi
Compression Method	MH, MR, MMR, JBIG
Memory Capacity	Up to 512 pages
Favourite Dials (in Address Book)	19 dials
Speed Dials (Coded Dials)	Up to 281 dials
Group Dials/Destination	Max. 299 dials/Max. 299 destinations
	Max. 310 destinations
Sequential Broadcast	
Sequential Broadcast Receive Mode	Fax Only, Manual, Answering, Fax/Tel Auto Switch
	Fax Only, Manual, Answering, Fax/Tel Auto Switch  Permanent fax memory backup. (Backup with flash memory)
Receive Mode	

Legal, Letter, Executive, Statement, OFICIO, B-OFICIO, M-OFICIO, LTR, LGL, Foolscap, Customs sizes: Min. 105 × 148.  Max. 216.0 × 355.6 mm.  Multi-purpose tray. A4, A5, A5 (Landscape), A6, B5, Legal, Lette Executive, Statement, OFICIO, B-OFICIO, M-OFICIO, G-LTR, GLGL, Foolscap, Post card, Index card, Envelope (COM), Monarch, C5, DLJ, Custom sizes: Min. 76.2 × 127 mm; Max. 21 × 355.6 mm.  ADF. A4, A5, A6, B5, Legal, Letter, Statement, Custom sizes: Min. 76.2 × 127 mm; Max. 21 × 355.6 mm.  ADF. A4, A5, A6, B5, Legal, Letter, Statement, Custom sizes: Min. 70.5 × 128 mm Max. 215.9 × 355.6 mm.  Paper Type  Plain paper, Recycled paper, Heavy Paper, Thin paper, Label, Pocard, Envelope  Paper Weight  Cassette (standard and optional): 60 to 120 gsm Multi-purpose tray. 60 to 199 gsm  ADF: 50 to 105 gsm  Connectivity and Software  Standard Interfaces  USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX/1000Base-T, Wireles 802.1tb/g/n, Wireless Direct Connection  Ves (Passive)  Near Field Communication  (NFC)  Network Protocol  Print: LPD, RAW, Port9100, IPP, IPPS, WSD (IPV4, IPV6)  Scan: Email, SMB, WSD-Scan (IPV4, IPV6), FTP-Scan, IFAX  TCPIP Application Services: Bonjour (mDNS), HTTP, HTTPS, PC  before SMTP (IPV4, IPV6), DHCP, ARP+PING, Auto IP, WINS  (IPV4), DHCPA'G (IPV6)  Management: SNMPM; SNMPV3 (IPV4, IPV6), STEP, HTTPS, PC  before SMTP (IPV4, IPV6), DHCP, ARP+PING, Auto IP, WINS  (IPV6), DHCPA'G (IPV6)  Management: SNMPM; SNMPV3 (IPV4, IPV6), SSC (IHTTI)  (IPPS)  Wireless: WEP (64/128 bit), WPA-PSK (TKIP/AES), WPA2-PSK (AE  One-Push Wireless  Configuration  Other Features  Department ID, Secure Print, Application Library  Workers: Power Status Tool, embedded RDS allows remote applies AirPrint*, Mopria* Print Service, Google Cloud Print Apple* AirPrint*, Mopria* Print Service  2008 Mac OS X v	Paper Handling	
Paper Output  250 sheets  Paper Size  Cassette (standard and optional): A4, A5, A5 (Landscape), A6, B Legal, Letter, Executive, Statement, OFICIO, B-OFICIO, M-OFICIO, LTR, LGI, Foolscap, Custom sizes: Min. 105 * 148 Max. 2160.* 355.6 mm.  Multi-purpose tray: A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, OFICIO, B-OFICIO, M-OFICIO, GLTR, Obstance, CG, DL), Custom sizes: Min. 76, 2 * 127 mm; Max. 21 * 255.6 mm.  ADF: A4, A5, A6, B5, Legal, Letter, Statement; Custom sizes: Min. 76, 2 * 127 mm; Max. 21 * 255.6 mm.  ADF: A4, A5, A6, B5, Legal, Letter, Statement; Custom sizes: Min. 76, 2 * 127 mm; Max. 21 * 255.6 mm.  ADF: A4, A5, A6, B5, Legal, Letter, Statement; Custom sizes: Min. 705 * 128 mm Max. 215.9 * 355.6 mm.  ADF: A4, A5, A6, B5, Legal, Letter, Statement; Custom sizes: Min. 105 * 128 mm Max. 215.9 * 355.6 mm.  Paper Type  Plain paper, Recycled paper, Heavy Paper, Thin paper, Label, Pocard, Envelope  Paper Weight  Cassette (standard and optional): 60 to 120 gsm Multi-purpose tray: 60 to 199 gsm. ADF: 50 to 105 gsm.  Connectivity and Software  Standard Interfaces  USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX/1000Base-T, Wirelet 802.11b/g/n, Wireless Direct Connection  Near Field Communication  (NFC)  Network Protocol  Print: LPD, RAW, Port9100, IPP, IPPS, WSD (IPV4, IPV6)  Scan: Email, SMB, WSD-Scan (IPV4, IPV6), FTP-Scan, IFAX TCP/IP Application Services: Bonjour (mDNS), HTTP, HTTPS, C before SMTP (IPV4, IPV6), DHCP, ARP-PING, Auto IP, WINS (IPV4), DHCPA (IPV6)  Metwork Security  Wired: IPMac address filtering, IEEE802.1X, SNMPV3, SSL (HTTI IPPS)  Wireless  Configuration  Other Features  Department ID, Secure Print, Application Library  Canon PRINT Business, Canon Print Service, Google Cloud Print Apple* AirPrint*, Mopria* Print Service  Address Book  LDAP  Compatible Operating  Systems  Officerver* 2012 R2/Server* 2012/Server* 2019/Server* 2019/Server	Paper Input (Based on 80 gsm)	100-sheet multi-purpose tray
Paper Size  Cassette (standard and optional): A4, A5, A5 (Landscape), A6, B Legal, Letter, Executive, Statement, OFICIO, B-OFICIO, MOR. 720, 00556, moliscap, Custom sizes, Min. 105 × 148 in Mor. 720, 00556, moliscap, Custom sizes, Min. 105 × 148 in Mor. 720, 00556, moliscap, Custom sizes, Min. 105 × 148 in Mor. 720, 00556, moliscap, Custom sizes, Min. 105 × 148 in Mor. 720, 00556, moliscap, Color, Mor. 720, 00556, moliscap, Color, Mor. 720, 00556, moliscap, Color, Mor. 720, 00556, mol. A55, 6 mm.  ADF: A4, A5, A6, B5, Legal, Letter, Statement; Custom sizes: Mir. 725, 2 × 127 mm; Max. 21 × 355, 6 mm.  Paper Type  Paper Weight  Cassette (standard and optional): 60 to 120 gsm Multi-purpose tray, 60 to 199 gsm. ADF: 50 to 105 gsm.  ADF: A4, A5, A6, B5, Legal, Letter, Statement; Custom sizes: Mir. 105 × 128 mm Max. 215, 9 × 355, 6 mm.  Paper Weight  Cassette (standard and optional): 60 to 120 gsm Multi-purpose tray, 60 to 199 gsm. ADF: 50 to 105 gsm.  ADF: A50 to 105 gsm.  Connectivity and Software  Standard Interfaces  USB 2.0 Hi-Speed, 108ASE-T/100BASE-TX/1000Base-T, Wireles 302.11b/g/n, Wireless Direct Connection  Ves (Passive)  Network Protocol  Print: LPD, RAW, Port9100, IPP, IPPS, WSD (IPV4, IPV6)  Scan: Email, SMB, WSD-Scan (IPV4, IPV6), FTP-Scan, IFAX TCPIP Application Services: Bonjour (mDNS), HTTP, HTTPS, PC before SMTP (IPV4, IPV6), DHCP, ARP+PING, Auto IP, WINS (IPV4), IPV6) (IPV6)  Management: SNMPN, SMMPv3 (IPV4, IPV6), WPA2-PSK (AE Onse-Push Wireless  Wirel: IPMac address filtering, IEEE802.IX, SNMPv3, SSL (HTTI IPPS)  Wireless: WEP (64/128 bit), WPA-PSK (TKIP/AES), WPA2-PSK (AE Onse-Push Wireless  Wirel: Pindare address filtering, IEEE802.IX, SNMPv3, SSL (HTTI IPPS)  Wireless: WEP (64/128 bit), WPA-PSK (TKIP/AES), WPA2-PSK (AE Onse-Push Wireless)  Wireless: WEP (64/128 bit), WPA-PSK (TKIP/AES), WPA2-PSK (AE Onse-Push Wireless)  Wireless: WEP (64/128 bit), WPA-PSK (TKIP/AES), WPA2-PSK (AE Onse-Push Wireless)  Wireless: WEP (64/128 bit), WPA-PSK (TKIP/AES), WPA2-PSK (AE Onse-Push Wireless)  Wireless: W	Maximum Paper Capacity	2,300 sheets
Legal, Letter, Executive, Statement, OFICIO, B-OFICIO, M-OFICIO, LTR, LGL, Foolscap, Customs sizes: Min. 105 × 148.  Max. 216.0 × 355.6 mm.  Multi-purpose tray. A4, A5, A5 (Landscape), A6, B5, Legal, Lette Executive, Statement, OFICIO, B-OFICIO, M-OFICIO, G-LTR, GLGL, Foolscap, Post card, Index card, Envelope (COM), Monarch, C5, DLJ, Custom sizes: Min. 76.2 × 127 mm; Max. 21 × 355.6 mm.  ADF. A4, A5, A6, B5, Legal, Letter, Statement, Custom sizes: Min. 76.2 × 127 mm; Max. 21 × 355.6 mm.  ADF. A4, A5, A6, B5, Legal, Letter, Statement, Custom sizes: Min. 70.5 × 128 mm Max. 215.9 × 355.6 mm.  Paper Type  Plain paper, Recycled paper, Heavy Paper, Thin paper, Label, Pocard, Envelope  Paper Weight  Cassette (standard and optional): 60 to 120 gsm Multi-purpose tray. 60 to 199 gsm  ADF: 50 to 105 gsm  Connectivity and Software  Standard Interfaces  USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX/1000Base-T, Wireles 802.1tb/g/n, Wireless Direct Connection  Ves (Passive)  Near Field Communication  (NFC)  Network Protocol  Print: LPD, RAW, Port9100, IPP, IPPS, WSD (IPV4, IPV6)  Scan: Email, SMB, WSD-Scan (IPV4, IPV6), FTP-Scan, IFAX  TCPIP Application Services: Bonjour (mDNS), HTTP, HTTPS, PC  before SMTP (IPV4, IPV6), DHCP, ARP+PING, Auto IP, WINS  (IPV4), DHCPA'G (IPV6)  Management: SNMPM; SNMPV3 (IPV4, IPV6), STEP, HTTPS, PC  before SMTP (IPV4, IPV6), DHCP, ARP+PING, Auto IP, WINS  (IPV6), DHCPA'G (IPV6)  Management: SNMPM; SNMPV3 (IPV4, IPV6), SSC (IHTTI)  (IPPS)  Wireless: WEP (64/128 bit), WPA-PSK (TKIP/AES), WPA2-PSK (AE  One-Push Wireless  Configuration  Other Features  Department ID, Secure Print, Application Library  Workers: Power Status Tool, embedded RDS allows remote applies AirPrint*, Mopria* Print Service, Google Cloud Print Apple* AirPrint*, Mopria* Print Service  2008 Mac OS X v	Paper Output	250 sheets
card, Envelope  Cassette (standard and optional): 60 to 120 gsm Moltit-purpose tray; 60 to 199 gsm ADF: 50 to 105 gsm  Connectivity and Software  Standard Interfaces  USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX/1000Base-T, Wireless Borect Connection  Near Field Communication (NFC)  Network Protocol  Print: LPD, RAW, Port9100, IPP, IPPS, WSD (IPV4, IPV6) Scan: Email, SMB, WSD-Scan (IPv4, IPV6), FTP-Scan, IFAX TCP/IP Application Services: Bonjour (mDNS), HTTP, HTTPS, PC before SMTP (IPV4, IPV6), DHCP, ARP+PING, Auto IP, WINS (IPV4), DHCPv6 (IPV6) Management: SNIMPV1, SNIMPv3 (IPV4, IPV6)  Network Security  Wired: IP/Mac address filtering, IEEE802.1X, SNIMPv3, SSL (HTTI IPPS) Wireless: WEP (64/128 bit), WPA-PSK (TKIP/AES), WPA2-PSK (AE One-Push Wireless  Wi-Fi Protected Setup (WPS)  Configuration  Other Features  Department ID, Secure Print, Application Library  Mobile Solution  Canon PRINT Business, Canon Print Service, Google Cloud Prin Apple® AirPrint*, Mopria® Print Service  Address Book  LDAP  Compatible Operating Systems  Windows® 10/Windows® 8.1/Windows® 7/Server® 2019/Server® 2018 R2/Server® 2012 R2/Server® 2012 R2/Server® 2008 Race on Unit Apple Management, Toner Status Tool, embedded RDS allows remote eMaintenance services such as meter capture, automatic consumables management and remote diagnostics. Universal Log-in Management and remote diagnostics. Universal Log-in Manager/uniFLOW online/uniFLOW online Express/  uniFLOW Compatibility, Application Library  General  Device Memory  1GB  LCD Display  WVGA Colour LCD 5.0* Touch Screen Display  Dimensions (W D × H)  494 mm × 464 mm × 452 mm  Weight  19.8 kg  Power Consumption  Maximum: Approx. 1,430 W  Standby: Approx. 1,340 W  Standby: Approx. 1,350 W  Steep mode: Approx. 0.9 W  Typical Electricity Consumption (TEC): 1.4 kWh/week (230 V)  Noise Level  Sound Pressure: Active: 72.9 dB; Standby: 24 dB  Sound Power: Active: 72.9 dB; Standby: 1 audible  Temperature: 10–30°C  Humidity: 20–80% RH (No Condensation)  Power Requirement  AC 220–240 V(±10%), 50/60 Hz(±2 Hz	Paper Size	M-OFICIO, LTR, LGL, Foolscap; Custom sizes: Min. 105 × 148 mm; Max. 216.0 × 355.6 mm.  Multi-purpose tray: A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, OFICIO, B-OFICIO, M-OFICIO, GLTR, GLGL, Foolscap, Post card, Index card, Envelope (COM10, Monarch, C5, DL); Custom sizes: Min. 76.2 × 127 mm; Max. 216.0 × 355.6 mm.  ADF: A4, A5, A6, B5, Legal, Letter, Statement; Custom sizes: Min.
Connectivity and Software  Standard Interfaces  USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX/1000Base-T, Wireles 802.11b/g/n, Wireless Direct Connection  Near Field Communication (NFC)  Network Protocol  Print: LPD, RAW, Port9100, IPP, IPPS, WSD (IPv4, IPv6) Scan: Email, SMB, WSD-Scan (IPv4, IPv6), FTP-Scan, IFAX TCP/IP Application Services: Bonjour (mDNS), HTTP, HTTPS, PC before SMTP (IPv4, IPv6), DHCPv8, RAPP-PING, Auto IP, WINS (IPv4), DHCPv6 (IPv6) Management: SNIMPv1, SNMPv3 (IPv4, IPv6), DHCPv6 Management: SNIMPv1, SNMPv3 (IPv4, IPv6), DHCPv4, IPv6) Mobile Solution  Other Features  Department ID, Secure Print, Application Library  Mobile Solution  Canon PRINT Business, Canon Print Service, Google Cloud Print Apple® AirPrint*, Mopria®	Paper Type	Plain paper, Recycled paper, Heavy Paper, Thin paper, Label, Post card, Envelope
Standard Interfaces  USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX/1000Base-T, Wireles 8021b/g/n, Wireless Direct Connection  Near Field Communication (NFC)  Network Protocol  Print: LPD, RAW, Port9100, IPP, IPPS, WSD (IPV4, IPV6) Scan: Email, SMB, WSD-Scan (IPV4, IPV6), FTP-Scan, IFAX TCP/IP Application Services: Bonjour (mDNS), HTTP, HTTPS, PC Defore SMTP (IPV4, IPV6), DHCP, ARP+PING, Auto IP, WINS (IPV4), DHCPv6 (IPV6) Management: SNMPv1, SNMPv3 (IPv4, IPV6) Mercess: WEP (64/128 bit), WPA-PSK (TKIP/AES), WPA2-PSK (AE One-Push Wireless Configuration  Other Features  Department ID, Secure Print, Application Library  Mobile Solution  Canon PRINT Business, Canon Print Service, Google Cloud Prin Apple® AirPrint", Mopria® Print Service  Address Book  LDAP  Windows® 10Windows® 8.1Windows® 7/Server® 2019/ Server® 2016/Server® 2012 R2/Server® 2012/Server® 2019 Server® 2016/Server® 2012 R2/Server® 2012/Server® 2019 Server® 2016/Server® 2012 R2/Server® 2012/Server® 2018 R2/Server® 2016/Server® 2012 R2/Server® 2012 R2/Server® 2016/Server® 2012 R2/Serve	Paper Weight	Multi-purpose tray: 60 to 199 gsm
Near Field Communication   Yes (Passive)	Connectivity and Software	
Network Protocol   Print: LPD, RAW, Port9100, IPP, IPPS, WSD (IPV4, IPV6)   Scan: Email, SMB, WSD-Scan (IPV4, IPV6), FTP-Scan, IFAX TCP/IP Application Services: Bonjour (mDNS), HTTP, HTTPS, PC before SMTP (IPV4, IPV6), DHCP, ARP+PING, Auto IP, WINS (IPV4), IPV6, IPV6)   DHCP, ARP+PING, Auto IP, WINS (IPV4), IPV6)   PV6, IPV6, IPV7,		-
Scan: Email, SMB, WSD-Scan (IPv4, IPv6), FTP-Scan, iFAX TCP/IP Application Services: Bonjour (mbNs), HTTP, HTTPS, PC before SMTP (IPv4, IPv6), DHCP, ARP+PING, Auto IP, WINS (IPv4), DHCPv6 (IPv6) Management: SNMPv1, SNMPv3, (IPv4, IPv6)  Network Security Wired: IP/Mac address filtering, IEEE802.1X, SNMPv3, SSL (HTTI IPPS) Wireless: WEP (64/128 bit), WPA-PSK (TKIP/AES), WPA2-PSK (AE One-Push Wireless Configuration Other Features Department ID, Secure Print, Application Library  Mobile Solution Canon PRINT Business, Canon Print Service, Google Cloud Prin Apple® AirPrint", Mopria® Print Service  Address Book LDAP Canon PRINT Business, Canon Print Service Google Cloud Prin Apple® AirPrint", Mopria® Print Service 2016/Server® 2018 R2/Server® 2016/Server® 2018 Rac OS Not4; Linux  Software Included MF Scan Utility, Remote User Interface (RUI), Department ID Management, Toner Status Tool, embedded RDS allows remote eMaintenance services such as meter capture, automatic consumables management and remote diagnostics. Universal Log-in Manager/uniFLOW online/uniFLOW online Express/ uniFLOW Compatibility, Application Library  General Device Memory 1GB  LCD Display WVGA Colour LCD 5.0" Touch Screen Display  Dimensions (W × D × H) 494 mm × 464 mm × 452 mm  Weight 19.8 kg  Power Consumption Maximum: Approx. 1,430 W Standby: Approx. 13.6 W Steep mode: Approx. 0.9 W Typical Electricity Consumption (TEC): 1.4 kWh/week (230 V)  Noise Level Sound Pressure: Active: 54 dB; Standby: Inaudible  Operating Environment Temperature: 10–30°C Humidity: 20–80% RH (No Condensation)  Power Requirement AC 220–240 V(±10%), 50/60 Hz(±2 Hz)  Toner Cartridge CART056H; yields 21,000 pages Printer ships with CART056L: 5,100 pages  Poptional Accessories  Paper Feeder PP-C1 (550 sheets), MiCard Attachment Kit-B1,		
IPPS  Wireless: WEP (64/128 bit), WPA-PSK (TKIP/AES), WPA2-PSK (AE One-Push Wireless Configuration	Network Protocol	Scan: Email, SMB, WSD-Scan (IPv4, IPv6), FTP-Scan, iFAX TCP/IP Application Services: Bonjour (mDNS), HTTP, HTTPS, POP before SMTP (IPv4, IPv6), DHCP, ARP+PING, Auto IP, WINS (IPv4), DHCPv6 (IPv6)
Wireless: WEP (64/128 bit), WPA-PSK (TKIP/AES), WPA2-PSK (AE One-Push Wireless Configuration Other Features Department ID, Secure Print, Application Library Mobile Solution Canon PRINT Business, Canon Print Service, Google Cloud Prin Apple® AirPrint", Mopria® Print Service Address Book LDAP Compatible Operating Systems 2016/Server® 2012 R2/Server® 2012/Server® 2019 Server® 2008 Mac OS X version 10.9.5 and up/Mac OS 10.14; Linux Software Included MF Scan Utility, Remote User Interface (RUI), Department ID Management, Toner Status Tool, embedded RDS allows remote eMaintenance services such as meter capture, automatic consumables management and remote diagnostics. Universal Log-in Manager/uniFLOW online/uniFLOW online Express/ uniFLOW Compatibility, Application Library  General Device Memory 1GB LCD Display WVGA Colour LCD 5.0" Touch Screen Display Dimensions (W × D × H) Weight 19.8 kg Power Consumption Maximum: Approx. 1,430 W Standby: Approx. 0.9 W Typical Electricity Consumption (TEC): 1.4 kWh/week (230 V) Noise Level Sound Pressure: Active: 54 dB; Standby: 24 dB Sound Prower: Active: 72.9 dB; Standby: Inaudible  Operating Environment Temperature: 10–30°C Humidity: 20–80% RH (No Condensation) Power Requirement AC 220–240 V(±10%), 50/60 Hz(±2 Hz)  CARTO56: yields 21,000 pages CARTO56H; yields 21,000 pages Printer ships with CARTO56L: 5,100 pages Optional Accessories Paper Feeder Paper Feeder PP-C1 (550 sheets), MiCard Attachment Kit-B1,	Network Security	Wired: IP/Mac address filtering, IEEE802.1X, SNMPv3, SSL (HTTPS,
Configuration Other Features Department ID, Secure Print, Application Library Mobile Solution Canon PRINT Business, Canon Print Service, Google Cloud Prin Apple® AirPrint", Mopria® Print Service Address Book LDAP Compatible Operating Systems Vindows® 10/Windows® 8.1/Windows® 7/Server® 2019/ Server® 2016/Server® 2012 R2/Server® 2012/Server® 2008 R2/Server® 2018 R2/Server® 2019 Server® 201		Wireless: WEP (64/128 bit), WPA-PSK (TKIP/AES), WPA2-PSK (AES)
Mobile Solution         Canon PRINT Business, Canon Print Service, Google Cloud Prin Apple® AirPrint", Mopria® Print Service           Address Book         LDAP           Compatible Operating Systems         Windows® 10/Windows® 8.1/Windows® 7/Server® 2019/ Server® 2008 R2/Server® 2008 Mac OS X version 10.9.5 and up/Mac OS 10.14; Linux           Software Included         MF Scan Utility, Remote User Interface (RUI), Department ID Management, Toner Status Tool, embedded RDS allows remote eMaintenance services such as meter capture, automatic consumables management and remote diagnostics. Universal Log-in Manager/uniFLOW online/uniFLOW online Express/ uniFLOW Compatibility, Application Library           General         Device Memory         1GB           LCD Display         WVGA Colour LCD 5.0" Touch Screen Display           Dimensions (W × D × H)         494 mm × 464 mm × 452 mm           Weight         19.8 kg           Power Consumption         Maximum: Approx. 1,430 W Standby: Approx. 0.9 W Typical Electricity Consumption (TEC): 1.4 kWh/week (230 V)           Noise Level         Sound Pressure: Active: 54 dB; Standby: 24 dB Sound Power: Active: 72.9 dB; Standby: Inaudible           Operating Environment         Temperature: 10–30°C Humidity: 20–80% RH (No Condensation)           Power Requirement         AC 220–240 V(±10%), 50/60 Hz(±2 Hz)           Toner Cartridge         CART1056: yields 21,000 pages Printer ships with CART056L: 5,100 pages           Printer ships with CART056L: 5,100 pages           Pa		Wi-Fi Protected Setup (WPS)
Apple® AirPrint", Mopria® Print Service  Address Book  LDAP  Compatible Operating Systems  2016/Server® 2012 R2/Server® 2012/Server® 2019/Server® 2018 R2/Server® 2018 R2/Serv	Other Features	Department ID, Secure Print, Application Library
Compatible Operating Systems  Windows® 10/Windows® 8:1/Windows® 7/Server® 2019/ Server® 2016/Server® 2018 R2/Server® 2018 R2/Server® 2018 R2/Server® 2008 R2/Server® 2019 R2/S	Mobile Solution	Canon PRINT Business, Canon Print Service, Google Cloud Print Apple AirPrint, Mopria Print Service
Systems 2016/Server® 2012 R2/Server® 2012/Server® 2008 R2/Server® 2008 Raz OS X version 10.9.5 and up/Mac OS 10.14; Linux  Software Included MF Scan Utility, Remote User Interface (RUI), Department ID Management, Toner Status Tool, embedded RDS allows remote eMaintenance services such as meter capture, automatic consumables management and remote diagnostics. Universal Log-in Manager/uniFLOW online/uniFLOW online Express/uniFLOW Compatibility, Application Library  General  Device Memory 1 GB  LCD Display WVGA Colour LCD 5.0" Touch Screen Display  Dimensions (W × D × H) 494 mm × 464 mm × 452 mm  Weight 19.8 kg  Power Consumption Maximum: Approx. 1,430 W Standby: Approx. 13.6 W Sleep mode: Approx. 0.9 W Typical Electricity Consumption (TEC): 1.4 kWh/week (230 V)  Noise Level Sound Pressure: Active: 54 dB; Standby: Inaudible  Operating Environment Temperature: 10–30°C Humidity: 20–80% RH (No Condensation)  Power Requirement AC 220–240 V(±10%), 50/60 Hz(±2 Hz)  Toner Cartridge CART1056H; yields 21,000 pages Printer ships with CART1056L: 5,100 pages  Optional Accessories  Paper Feeder Paper Feeder PF-C1 (550 sheets), MiCard Attachment Kit-B1,	Address Book	LDAP
Management, Toner Status Tool, embedded RDS allows remote eMaintenance services such as meter capture, automatic consumables management and remote diagnostics. Universal Log-in Manager/uniFLOW online/uniFLOW online Express/ uniFLOW Compatibility, Application Library  General  Device Memory 1GB  LCD Display WVGA Colour LCD 5.0" Touch Screen Display  Dimensions (W × D × H) 494 mm × 464 mm × 452 mm  Weight 19.8 kg  Power Consumption Maximum: Approx. 1,430 W Standby: Approx. 13.6 W Sleep mode: Approx. 0.9 W Typical Electricity Consumption (TEC): 1.4 kWh/week (230 V)  Noise Level Sound Pressure: Active: 54 dB; Standby: Laudible  Operating Environment Temperature: 10–30°C Humidity: 20–80% RH (No Condensation)  Power Requirement AC 220–240 V(±10%), 50/60 Hz(±2 Hz)  Toner Cartridge CART1056H; yields 21,000 pages Printer ships with CART1056L: 5,100 pages  Optional Accessories  Paper Feeder Paper Feeder PF-C1 (550 sheets), MiCard Attachment Kit-B1,		2016/Server® 2012 R2/Server® 2012/Server® 2008 R2/Server®
Device Memory         1 GB           LCD Display         WVGA Colour LCD 5.0" Touch Screen Display           Dimensions (W × D × H)         494 mm × 464 mm × 452 mm           Weight         19.8 kg           Power Consumption         Maximum: Approx. 13.6 W Standby: Approx. 0.9 W Typical Electricity Consumption (TEC): 1.4 kWh/week (230 V)           Noise Level         Sound Pressure: Active: 54 dB; Standby: 24 dB Sound Power: Active: 72.9 dB; Standby: Inaudible           Operating Environment         Temperature: 10−30°C Humidity: 20−80% RH (No Condensation)           Power Requirement         AC 220−240 V(±10%), 50/60 Hz(±2 Hz)           Toner Cartridge         CART1056: yields 10,000 pages CART056H: yields 21,000 pages Printer ships with CART056L: 5,100 pages           Monthly Duty Cycle         150,000 pages           Optional Accessories         Paper Feeder PF-C1 (550 sheets), MiCard Attachment Kit-B1,	Software Included	Management, Toner Status Tool, embedded RDS allows remote eMaintenance services such as meter capture, automatic consumables management and remote diagnostics. Universal Log-in Manager/uniFLOW online/uniFLOW online Express/
LCD Display         WVGA Colour LCD 5.0" Touch Screen Display           Dimensions (W × D × H)         494 mm × 464 mm × 452 mm           Weight         19.8 kg           Power Consumption         Maximum: Approx. 1,430 W Standby: Approx. 0.9 W Typical Electricity Consumption (TEC): 1.4 kWh/week (230 V)           Noise Level         Sound Pressure: Active: 54 dB; Standby: 24 dB Sound Power: Active: 72.9 dB; Standby: Inaudible           Operating Environment         Temperature: 10−30°C Humidity: 20−80% RH (No Condensation)           Power Requirement         AC 220−240 V(±10%), 50/60 Hz(±2 Hz)           Toner Cartridge         CART056: yields 10,000 pages CART056H; yields 21,000 pages Printer ships with CART056L: 5,100 pages           Monthly Duty Cycle         150,000 pages           Optional Accessories         Paper Feeder PF-C1 (550 sheets), MiCard Attachment Kit-B1,	General	
Dimensions (W × D × H)         494 mm × 464 mm × 452 mm           Weight         19.8 kg           Power Consumption         Maximum: Approx. 1,430 W Standby: Approx. 13.6 W Sleep mode: Approx. 0.9 W Typical Electricity Consumption (TEC): 1.4 kWh/week (230 V)           Noise Level         Sound Pressure: Active: 54 dB; Standby: 24 dB Sound Power: Active: 72.9 dB; Standby: Inaudible           Operating Environment         Temperature: 10−30°C Humidity: 20−80% RH (No Condensation)           Power Requirement         AC 220−240 V(±10%), 50/60 Hz(±2 Hz)           Toner Cartridge         CART056: yields 10,000 pages CART056H: yields 21,000 pages Printer ships with CART056L: 5,100 pages           Monthly Duty Cycle         150,000 pages           Optional Accessories         Paper Feeder PF-C1 (550 sheets), MiCard Attachment Kit-B1,	Device Memory	1GB
Weight 19.8 kg  Power Consumption Maximum: Approx. 1,430 W Standby: Approx. 13.6 W Sleep mode: Approx. 0.9 W Typical Electricity Consumption (TEC): 1.4 kWh/week (230 V)  Noise Level Sound Pressure: Active: 54 dB; Standby: 24 dB Sound Power: Active: 72.9 dB; Standby: Inaudible  Operating Environment Temperature: 10–30°C Humidity: 20–80% RH (No Condensation)  Power Requirement AC 220–240 V(±10%), 50/60 Hz(±2 Hz)  Toner Cartridge CART056: yields 10,000 pages CART056H: yields 21,000 pages Printer ships with CART056L: 5,100 pages  Monthly Duty Cycle Dytional Accessories  Paper Feeder Paper Feeder PF-C1 (550 sheets), MiCard Attachment Kit-B1,		
Power Consumption  Maximum: Approx. 1,430 W Standby: Approx. 13.6 W Sleep mode: Approx. 0.9 W Typical Electricity Consumption (TEC): 1.4 kWh/week (230 V)  Noise Level  Sound Pressure: Active: 72.9 dB; Standby: 14 dB Sound Power: Active: 72.9 dB; Standby: Inaudible  Operating Environment  Temperature: 10–30°C Humidity: 20–80% RH (No Condensation)  Power Requirement  AC 220–240 V(±10%), 50/60 Hz(±2 Hz)  Toner Cartridge  CART056: yields 10,000 pages CART056: yields 21,000 pages Printer ships with CART056L: 5,100 pages  Monthly Duty Cycle  Optional Accessories  Paper Feeder  Paper Feeder PF-C1 (550 sheets), MiCard Attachment Kit-B1,		
Sound Power: Active: 72.9 dB; Standby. Inaudible		Maximum: Approx. 1,430 W Standby: Approx. 13.6 W Sleep mode: Approx. 0.9 W
Humidity: 20-80% RH (No Condensation)	Noise Level	
Toner Cartridge CART056: yields 10,000 pages CART056H: yields 21,000 pages Printer ships with CART056L: 5,100 pages  Monthly Duty Cycle 150,000 pages  Optional Accessories  Paper Feeder Paper Feeder PF-C1 (550 sheets), MiCard Attachment Kit-B1,	Operating Environment	Temperature: 10–30°C Humidity: 20–80% RH (No Condensation)
CART056H: yields 21,000 pages Printer ships with CART056L: 5,100 pages  Monthly Duty Cycle 150,000 pages  Optional Accessories  Paper Feeder Paper Feeder PF-C1 (550 sheets), MiCard Attachment Kit-B1,	Power Requirement	AC 220–240 V(±10%), 50/60 Hz(±2 Hz)
Optional Accessories  Paper Feeder PF-C1 (550 sheets), MiCard Attachment Kit-B1,	Toner Cartridge	CART056H: yields 21,000 pages
Paper Feeder PF-C1 (550 sheets), MiCard Attachment Kit-B1,	Monthly Duty Cycle	150,000 pages
	Optional Accessories	
Barcode Printing Kit-E1	Paper Feeder	Paper Feeder PF-C1 (550 sheets), MiCard Attachment Kit-B1, Barcode Printing Kit-E1

For information and services contact

Canon Australia Pty Ltd Canon New Zealand Ltd

1800 444 199 0800 222 666

canon.com.au/business canon.co.nz/business



