

PIXMA TS9565



no one sees it like you

Canon

A3 PIXMA HOME TS9565

YOUR A3 CRAFT PRINTER



Wireless

Print with ease with PIXMA Cloud Print and other applications such as Apple AirPrint, Google Cloud Print that simply connect to mobile devices.



Print With New Media

Get creative and use your printer to print on a variety of new mediums such as nail stickers, 12" x 12" card stock (for scrapbooking and card making), 5" x 15" and 3.5" x 3.5" square sizes, restickable and magnetic paper.



A3

Perfect for the home or office, this compact multi function printer with automatic document feeder (ADF) can print up to A3 size without being bulky or appearing oversized.



Redefined inks

Produce crisp text with pigment black, beautiful photos with 5-color independent inks.



Borderless Printing

Borderless Prints

Print your documents and photos on a range of different paper sizes, from business card to Instagram-style images, on square sizes! You can even print borderless 4"x6" photos in approx. 17 seconds.



Dual Paper Feeder & auto two-sided printing

Get flexible with the way your printer receives paper – either through rear paper feeding or via front paper cassette. The paper output tray is automatically expandable, as well as two sided printing.



Booklet layout printing

Print booklets with ease using A3 and A4 paper. Perfect for holiday itineraries, recipe books, colouring books and your business needs.



Printable Nail Stickers Print

Printable Nail Stickers

Change up your look daily and print any picture or pattern on to stick on nail stickers.



Memory Card

SD Card Reader

Print photos off your laptop or camera, with the printer's direct SD card slot - making it easier than ever before to showcase your prints.



Built-In Pattern Paper

45 built-in patterned papers makes creative printing and scrapbooking easy. Print directly from your printer in minutes without the use of your PC.

What inks can I use with my printer?



Ink Yield 680 A4 document: 600 4"x6" photo: 500 **Ink Yield** 680 A4 document: 400 4"x6" photo: 333 **Ink Yield** 680 A4 document: 200 4"x6" photo: 166 **Ink Yield** 681 A4 document: 820 4"x6" photo: 282 **Ink Yield** 681 A4 document: 515 4"x6" photo: 170 **Ink Yield** 681 A4 document: 310 4"x6" photo: 83 **Ink Yield** 681 A4 document: 760 4"x6" photo: 307 **Ink Yield** 681 A4 document: 474 4"x6" photo: 235 **Ink Yield** 681 A4 document: 237 4"x6" photo: 108 **Ink Yield** 681 A4 document: 824 4"x6" photo: 322 **Ink Yield** 681 A4 document: 514 4"x6" photo: 199 **Ink Yield** 681 A4 document: 257 4"x6" photo: 99 **Ink Yield** 681 A4 document: 6360 4"x6" photo: 858 **Ink Yield** 681 A4 document: 3120 4"x6" photo: 520 **Ink Yield** 681 A4 document: 1451 4"x6" photo: 231

no one sees it like you

Canon

Technical Specifications

PIXMA HOME TS9565

Print Head / Ink	Type		Permanent
	Number of Nozzles Ink Tank		Total 4,096 nozzles (PGBK 1,024 nozzles, BK/Y each 512 nozzles, C/M each 1,024 nozzles) 5-color(C/M/Y/BK/PGBK)
Maximum Printing Resolution			4800 (horizontal) ² x 1200 (vertical) dpi
Print Speed	Document : Col ³	ESAT/Simplex	approx. 10.0 ipm
	Document : B/W ³	ESAT/Simplex	approx. 15.0 ipm
	Document : Col ³	FPOT Ready/Simplex	approx. 10.0 sec.
	Document : B/W ³	FPOT Ready/Simplex	approx. 8.0 sec.
	Photo (4"x6") ³	PP-201/Borderless	approx. 21 sec
Printable Width			Up to 298.0mm, Borderless: Up to 304.8mm
Printable Area	Borderless Printing ⁴		Top/Bottom/Right/Left margin: each 0 mm
	Bordered Printing		Top margin: 3 mm, Bottom margin: 5 mm, Left/Right margin: each 3.4 mm (LTR/LGL: Left: 6.4 mm, Right: 6.3 mm)
	Bordered Auto 2-sided printing		Top margin: 5 mm, Bottom margin: 5 mm, Left/Right margin: 3.4 mm (LTR: Left: 6.4 mm, Right: 6.3 mm)
Support Media	Rear Tray		Plain Paper, Photo Paper Pro Platinum (PT-101), Photo Paper Pro Luster (LU-101), High Resolution Paper (HR-101N), Photo Paper Plus Glossy II (PP-301) Photo Paper Pro Luster (LU-101), Photo Paper Plus Semi-gloss (SG-201), Photo Paper Glossy (GP-701) Matte Photo Paper (MP-101), T-Shirt Transfer, Envelope, Greeting Card (manufactured by Avery and RedRiverPaper), Cardstock, Magnetic Photo Paper(MG-101)Restickable Photo Paper(RP-101)
	Cassette Multi-purpose Tray		Plain Paper Printable Nail Stickers (NL-101)
Paper Size	Rear Tray		A4, A5, B5, LTR, LGL, LDR, B4, A3, Envelopes(DL, COM10), Square (5"x5", 4"x4", 3.5"x3.5"), Card Size(91 x 55mm), 4"x6", 5"x7",7"x10", 8"x10", 10"x12", 12"x12" [Custom size] width 55mm - 304.8 mm, length 89mm - 676mm
	Cassette		A4, A5, B5, LTR [Custom size] width 148.0 mm - 215.9 mm, length 210mm - 297mm
Paper Size (Borderless)			A4, A3, LTR, LDR, 4"x6",5"x7",7"x10", 8"x10",10"x12", 12"x12"Card Size(91x55mm), Square (5"x5", 4"x4", 3.5"x3.5")
Paper Handling (Maximum Number)	Rear Tray	Plain Paper (LTR size)	Plain Paper= 100
		Plain Paper (A4 size)	Plain Paper, Canon Red Label Superior(WOP111) = 100 Canon Oce Office Colour Paper(SAT213) = 80 * A3 size : Plain Paper = 50
	Cassette	Plain Paper (LTR size)	Plain Paper=100
		Plain Paper (A4 size)	Plain Paper, Canon Oce Red Label Paper(WOP111)= 100 Canon Oce Office Colour Paper(SAT213) = 80
	Multi-purpose Tray		1sheet (manual bypass)
Support Media for Auto 2-sided printing	Type		Plain Paper
	Size		A4, A5, B5, LTR
Paper Weight	Rear Tray		Plain Paper: 64-105 g/m ² , Canon specialty paper: max paper weight : approx. 300 g/m ² (Photo Paper Pro Platinum PT-101)
	Cassette		Plain Paper: 64-105 g/m ²
Ink End Sensor			Dot count
Print Head Alignment			Auto/Manual

no one sees it like you

Technical Specifications

PIXMA HOME TS9565

SCAN ⁵	Scanner Type			Flatbed	
	Scanning Method			CIS	
	Optical Resolution ⁶	*Optical resolution scan is available, only when you use TWAIN Driver.		1200 x 2400 dpi	
	Scanning Bit Depth (Input/Output)	Grayscale		16bit/8bit	
		Color		RGB each 16bit/8bit	
COPY	Maximum Document Size	Flatbed		A4/LTR(216 x 297mm)	
		ADF		A4/LTR/LGL	
	Compatible Media	Size		A4/A5/B5/LTR/LGL/B4/A3/11"x17"/LDR/4"x6"/5"x7"/Square (5" x 5")/Card Size(91 x 55mm)/Disc Label	
		Type		Plain Paper, Photo Paper Pro Platinum (PT-101), Photo Paper Pro Luster (LU-101), Photo Paper Plus semi-gloss (SG-201), Photo Paper Glossy (GP-701) , Matte Photo Paper(MP-101), Photo Paper Plus Glossy II (PP-301), Printable Disc	
	Image Quality			3 positions (Draft, Standard, High)	
	Density Adjustment			9 positions, Auto intensity(AE copy)	
	Copy Speed ¹⁰	Document : Color	sFCOT/Simplex		approx. 19 sec.
			sESAT/Simplex		approx. 6.5 ipm
		Document (ADF) : Color	ESAT/Simplex		approx. 8.0 ipm
	Multiple Copy	Document (ADF) : Black	ESAT/Simplex		approx. 14.0 ipm
Black/Color				max. 99 pages	
N/W	Protocol			TCP/IP	
	Wired LAN	Network Type		IEEE802.3u(100BASE-TX)/IEEE802.3(10BASE-T)	
		Data Rate			10M/100Mbps (auto switchable)
	Wireless LAN	Network Type			IEEE802.11n/IEEE802.11g/IEEE802.11b
		Frequency Band			2.4GHz
		Channel			1-13
		Range			indoor 50m (depends on the transmission speed and conditions)
	Security			WEP64/128bit WPA-PSK(TKIP/AES) WPA2-PSK(TKIP/AES)	
Direct connection(Wireless LAN)				Available	
Bluetooth				Available	
Printing Solutions	AirPrint			Available	
		Layout	bordered/borderless ¹⁵	LTR,A4,4"x6",5"x7",8"x10",Square (5"x5", 4"x4", 3.5"x3.5"), Card Size(91 x 55mm) , 7"x10, A3, LDR,10"x12", 12"x12"	
		Print Quality ¹²	(bordered only)		A5, B5, LGL, #10 Envelope, DL Envelope, Disc Label, B4, Custom size Standard/High
	Windows 10 Mobile, Mopria, Google Cloud Print, Canon Print Service, PIXMA Cloud Link				Available
	Canon PRINT Inkjet/SELPHY (for iOS/for Android)				Available
		Layout	1-up (bordered/borderless ¹⁵)		LTR, A4, 4"x6", 5"x7", 8"x10",Square (5"x5", 4"x4", 3.5"x3.5"),Card Size(91 x 55mm) ,A3, 10"x12",12"x12"
			1-up(borderd only)		A5, B5, LGL,B4
	Camera Direct Spec.	Compatible Digital Camera		"PictBridge" compliant digital cameras, camcorders and camera phones	
		Connecting type		LAN/ WLAN	
		File Format		JPEG (Exif ver2.2/2.21/2.3 compliant) ¹⁸ , PNG	
Card Direct Spec.	Compatible Storages			SD Card, SDHC Card, SDXC Card, miniSD Card ¹¹ , micro SD Card ¹¹ mini SDHC Card ¹¹ , micro SDHC Card ¹¹ , microSDXC Card ¹¹	
	File Format			JPEG and TIFF (Exif-compliant) taken by DCF(Ver.1.0/2.0) compliant digital cameras. (Exif ver2.2/2.21/2.3 compliant)	
	Storage function ¹⁴	READ Function		Available	
		WRITE Function		Available	
General Specifications	Operation Panel	Display		LCD (4.3 inch/10.8 cm TFT color)	
	ADF	Paper Handling (Plain Paper)		A4/LTR=20 sheet LGL=5 sheet	
		Auto Duplex		N/A	
	Interface	USB B Port			Hi-Speed USB
		Card Slots			Available
	PictBridge	Wireless LAN			Available
		LAN			Available
		USB			N/A
	Self-opening Paper Output Tray			N/A	
	Quiet Mode			Available	
	Acoustic Noise (PC Print)	Plain Paper(A4, B/W) ²⁷			Approx. 49.5 dB(A)
	Power				AC 100-240V 50/60Hz
	Power Consumption	OFF			Approx. 0.3 W
		Standby			Approx. 2.0 W
		Copying ²⁸			Approx. 14W
	Duty Cycle	USB connection to PC			25,000 Sheet
	Dimension(WxDxH)	Factory configuration	mm		Approx. 468 x 366 x 193 mm
Paper installed (cassette)		mm		As of factory configuration	
Output/ADF trays extended		mm		Approx. 468 x 820 x 373 mm	
Weight	kg			Approx. 9.7 kg	

no one sees it like you

Canon

- *2: Ink droplets can be placed with a pitch of 1/4800 inch at minimum.
- *3: Document print speeds are the averages of ESAT (Word, Excel, PDF) in Office Category Test for the default simplex mode, ISO/IEC 24734. Photo print speed is based on the default setting using ISO/JIS-SCID N2 on Photo Paper Plus Glossy II and does not take into account data processing time on host computer. Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.
- *5: TWAIN driver (ScanGear) is based on the TWAIN specification V1.9 and requires the Data Source Manager comes with the operating system.
- *6: Optical resolution is a measure of maximum hardware sampling resolution, based on ISO 14473 standard.
- *8: The fastest speed in Hi-Speed USB on Windows PC. Transfer time to computer is not included.
- *10: Copy speeds are the average of sFCOT and sESAT, ISO/IEC 29183. Copy speeds (ADF) are ESAT of copy in sequence, ISO/IEC24735. Copy speed may vary depending on document complexity, copy mode, page coverage, type of paper used etc. and does not take into account warming up time.
- *11: Can be used by attaching the adapter that is separately sold in the market.
- *12: Resolution may be changed between Direct print and printing from PC.
- *14: It is NOT supported via Network.
- *15: The amount of image extension beyond the paper cannot be adjusted.
- *16: Plain paper is printed bordered automatically, regardless of the camera settings.
- *17: Not supported for disk label print.
- *18: Image data taken by DCF (Ver.1.0/2.0)-compliant digital cameras, camcorders or camera phones and recorded in JPEG (Exif-compliant) format.
- *19: Function depends on the connected digital cameras, camcorders or camera phones.
- *20: Only 'high' mode available as for the printer without LCD.
- *23: *Non-support for 2/4/9/16-up in sticker printing as well as date/file number printing in disc label printing. As for '4-up' print layout, either file number or date can be printed at one time."
- *24: The performance of the printer may be reduced under certain temperature and humidity conditions.
- *25: For the temperature and humidity conditions of papers such as photo paper, refer to the paper's packaging or the supplied instructions.
- *26: When printing ISO/JIS-SCID N2 on 4"x6" Photo Paper Plus Glossy II using default settings.
- *27: Acoustic Noise is measured based on ISO7779 standard with default setting.
- *28: Copy: When copying ISO/JIS-SCID N2 (printed by inkjet printer) on A4 size plain paper using default settings. Specifications are subject to change without notice.
- *29: F11 in US, CND, LTN, BRA, TW and HK.
- *31: Black & white document fax transmission speed is based on default setting using ITU-T No.1 chart. Color document fax transmission speed is based on default setting using Canon Color Fax Test Sheet. Actual transmission speed may vary depending on document complexity, fax settings at receiving end, and line conditions etc.
- *32: Page count is based on ITU-T No.1 chart or Canon FAX Standard Chart No.1.
- *33: Not supported for AirPrint.
- *34: Typical Electricity Consumption (TEC) value: TEC value was calculated assuming the unit will be constantly switched among operational mode, sleep mode, and power-off mode for 5 days, and that it will be either in sleep or power-off mode for the remaining 2 days within the same week. The TEC value of this product is calculated by Canon on their own accord using TEC measurement procedure regulated in International ENERGY STAR Program.
- *35: Not supported for Printable Nail Stickers.

no one sees it like you

Canon