HP Color LaserJet Pro MFP M183fw



Get high-quality colour, wireless printing, and smart mobility and security solutions.2

An efficient, wireless MFP with fax for high-quality colour and productivity. Save time with Smart Tasks in HP Smart app and print and scan from your phone.² Get seamless connections and security essentials to help maintain privacy and control.





Freedom to work anywhere

- Get easy printing and scanning from your mobile device, with HP Smart best-in-class mobile print app.^{2,3}
- Eliminate steps in repetitive tasks with customizable shortcuts, with Smart Tasks in HP Smart app. Scan to the cloud, email, and more – in just a tap.2
- Organize documents 50% faster with Smart Tasks⁴ first mobile print app that automates scanning tasks.⁵
- Get notifications when printing, scanning, or copying from your mobile device, using HP Smart app.²



Trusted HP quality and performance

- Get high-quality colour and peak printing performance with Original HP Toner cartridges with JetIntelligence.
- Breeze through tasks with a 35-page automatic document feeder.
- Get guick and easy printing, copying, scanning, and faxing directly at the control panel.
- Help save energy with HP Auto-On/Auto-Off Technology and this ENERGY STAR® certified colour laser MFP.6



Security essentials, reliable connections

- · Security essentials to help maintain privacy and control, including basic encryption and password protection.
- Get faster, more reliable connections with dual band Wi-Fi®.7
- Easily share resources access and print with wireless and Ethernet networking.¹
- Connect your mobile device directly to your printer and easily print without accessing a network.⁸
- Wireless operations are compatible with 2.4 GHz and 5.0 GHz operations only. Learn more at hp.com/go/mobileprinting
- Requires the HP Smart app download. For details on local printing requirements see hp.com/go/mobileprinting. Certain features/software are available in English language only.
 Compared to OEM mobile printing apps for the majority of top-selling inkjet & laser printers & all-in-ones for home & home office, priced less than or equal to \$429.99 USD. Market share as reported by
- IDC CYQ2 2018 Hardcopy Peripherals Tracker. Claim based on research of printer manufacturer's mobile print apps and Keypoint Intelligence Buyers Lab hands-on testing and study commissioned by HP. See September 2018 report at keypointintelligence.com/HPSmartApp
- Based on internal HP testing. Average timing estimate based on: 1) downloaded HP Smart app on mobile or desktop device, 2) setting up Smart Tasks shortcut, 3) scanning jobs which have more than 2-3 tasks associated with them (scan to email, save and rename, store to cloud, etc.). Average timing savings comparison based on using printer and desktop scan software to complete similar scanning tasks. Requires the HP Smart app download and supported HP printer. For details on local printing requirements see hp.com/go/mobileprinting. Certain features/software are available in English language only.
- Compared to the majority of competing in-class consumer colour desktop inkjet all-in-ones <\$299 USD. Keypoint Intelligence Buyers Lab 2018 research study commissioned by HP based on research survey of printer manufacturers' published specifications, sustainability reports and press releases as of 12/15/2018 and not confirmed by lab testing. Market share as reported by IDC CYQ3 2018

 Hardcopy Peripherals Tracker, CYQ3 2018 Release. The ability to automate work defined as having the capability to use the OEM mobile print app to create a multistep workflow on mobile device and have a shortcut appear on the app and/or on control panel of printer; and/or use intelligent Optical Character Recognition to name a scanned file based on the first few words of a document. For more details, see $\frac{keypoint intelligence.com/HPOfficeJetPro}{HPAuto-On/Auto-Off Technology capabilities subject to printer and settings; may require a firmware upgrade.}$
- Wireless operations are compatible with 2.4 GHz and 5.0 GHz operations only. Learn more at hp.com/go/mobileprinting. Wi-Fi is a registered trademark of Wi-Fi Alliance®. Supports both 5.0 GHz and 2.4 GHz using up to 12 non-overlapping channels vs only 3 non-overlapping channels for 2.4 GHz only. Supports 5.0 GHz band (up to 150 mbps) vs 2.4 GHz band (up to 72.2 mbps).
- Mobile device needs to be connected to Wi-Fi Direct® signal of a Wi-Fi Direct-supported AiO or printer prior to printing. Details at hp.com/go/mobileprinting. Wi-Fi Direct® is a registered trademark of Wi-Fi Alliance®

Technical specifications

The Control of Control	Number of user Functions	1-5 Users Print, Copy, Scan, Fax, Wireless
Debe progressor Maile Area Format Act (big in 15 years) (and to 15 years) Maile Area Format Act (big in 15 years) (and to 15 years) Maile Area Format Act (big in 15 years) Maile Area Format Act (bi	Print	
Best formal, Abit 13s to 15 grant (Seed Formal, Abi		
Color (M. Speech Print Color of 18 Secretifs Besch also incloselyses Besch also incloselyses Company (19 Secretifs) Compan		Black (normal, A4): Up to 16 ppm; Colour (normal, A4): Up to 16 ppm; Black (Portrait, A5): Up to 5 ppm; Colour (Portrait, A5): Up to 5 ppm
International Content of the Conte	First page out ³	
Centrope contrainer		Up to 600 x 600 dpi
Sential per la language Fine terre prison prison prison per la per la personal perso		
Terminally Treatment of Shaper And College Could Prince producted that College Could Prince product Shaper And College Could Prince producted that College Could Prince producted Shaper College Colleg		HP PCL6; HP PCL5c; HP postscript level 3 emulation; PWG raster; PDF; PCLm; PCLm-S; URF
Pieter amangement Protes manutary brown Welches protests protest of the Control of the Period Republished Control of the Con	Energy Savings Feature	HP Auto-On/Auto-Off Technology; Instant-on Technology
Accordance Offliesterology, 169 years ago, sent pask shortness in 149 Smart pag, 159 seledentings secure bring. Sentencing Certain transp. Sentencing Certain transp. Sentencing Annual Sentencing Certain transp. Sentencing Annual Sentencing Certain transp. Sentencing Certain transport transport Certain transpo		
Expect Composition (1985) and Laborater of the Country of Section (1985) and Laborater of Laborater of Section (1985) and Laborater of Laborat		Wireless printing, Ethernet networking, Wireless direct printing, HP ePrint, Apple AirPrint™, Mopria-certified, Google Cloud Print, HP Auto-On/Auto-Off technology, HP Smart App, Smart task shortcuts in HP Smart App, HP JetAdvantage Secure Print
Resolution Mardiance ID 2007 (2004) to 200 Accordance and mons, AGP1, Up to 1200 - 1200 delication and mons, full bellio Optical Lip to 100 delication and mons, CPI (100 to 100 delication) and		Flathed ADE
And scarrent gives And sc		
Begiete 1965 File formal 9.5 (6.000 (8946), 1966, 1197 (1975) File formal 9.5 (6.000 (8946), 1966, 1197 (1975), 1966 (1975),		
Bit femals Fig. Span Stay P. P. Start Front 2-2-51 (column) Fig. Engine Land Fig. Span Stay P. P. Start Front Start Copy, Inc., 117 Start		
Somer advanced features Somera advanced features Somera advanced features Somera advanced features Somera discontinued features Butch General Act South of 2006 features Butch General Butch General Act South of 2006 features Butch General Butch General Act South of 2006 features Butch General Butch General Act South of 2006 features Butch General Butch Gen		
Scanne advanced features Pol-caming software 52 - Sheet Automatic Document Feeder (ARD) for unattended scanning of multiple pages, automatics can corpor from the control of the Deck Sheet Port (PCL Sheet as extended the Beet PCP)		
Soan to Secopid Developing Des (PDL Scan to Princesof One Drive, Share Port PDL Save as elabate file fleet, PDF) Asia document feedin capacity Standard, 35 obers Standard, 35 obers Back (ARQ As East 2) 1 Windows of printing First capy out* Back (ARQ As East 2) 2 seconds; Colour (ARQ). As East 23 17 9 seconds Back (ARQ As East 2) 2 seconds; Colour (ARQ). As East 23 17 9 seconds Back (ARQ As East 22 seconds; Colour (ARQ). As East 23 17 9 seconds Back (ARQ As East 22 seconds; Colour (ARQ). As East 23 17 9 seconds Back (ARQ As East 22 seconds; Colour (ARQ). As East 23 17 9 seconds Back (ARQ As East 22 seconds; Colour (ARQ). As East 23 17 9 seconds Locur to Standard (ARQ). As East 23 18 seconds; Colour (ARQ). As East 23 17 9 seconds Copier serial software features Lot 10 9 multiple copies. Reduce/Enlarge in Copie (ARQ). As East 23 18 seconds (ARQ). As East 24 18 secon		
Successful Standard, 15 clares. Speed Standard, 25 clares. Speed Standard, 25 clares. Speed Standard, 26 clare to 12 ceromb; Colour formal, A4): Up to 16 cpm. Speed Standard, 26 clare to 15 ceromb; Colour formal, A4): Up to 16 cpm. Macropros. Speed Standard, 26 clares. Also to Standard, 26 clares. Speed Standard, 26 clares. Also to Standard, 26 clares. Speed Standard, 26 clares. Also to Standard, 26 clares. Also to Standard, 26 clares. Speed Standard, 26 clares. Speed Standard, 26 clares. Speed Standard, 26 clares. Also to Standard, 26 clares. Speed Standard, 2		Scan to Google Drive/Drop box (PC); Scan to FTP(PC); Scan to Microsoft One Drive, Share Point (PC); Save as editable file (text, PDF)
Speed Black Genmal, Add to to 16 com. Colour formal, Add to 10 16 com Colour formal, Add to 10 16 com Colour formal, Add to 10 18 colour formal, Add	Auto document feeder capacity	
First copy out* Black CAPE As ford as 122 seconds. Colour (AAL): As fast as 179 seconds Up to 90 poins Copier rectance (Copier rectance) Copier senter for fewer features Copier senter for fewer features Lip to 99 multiple copiers. Rectanglife reper Lighter/Burker, Optimize, Paper, Mailt-page copy, Collation, Draft Mode; Image Adjustment; Set as Copier senter for fewer features Lip to 99 multiple copiers. Rectanglife		Black (normal, A4): Up to 16 cpm; Colour (normal, A4): Up to 16 cpm
Copier sertant Software Features Ambier of copies: Seeding of copies:	First copy out ⁴	Black (A4): As fast as 12.2 seconds; Colour (A4): As fast as 17.9 seconds
Copies senting Namber of copies, Reduce/Enlarge Lighter/Dakers, Optimizer, Depair, May Depair, Markey Reducer, Sentary, Reducer, Reducer, Reducer, Sentary,		
Copres mark software features Contract (glipter/dasken), 10-pp. (plennize copy selection feath presents autoselect, mixed printed prin		Number of copies; Reduce/Enlarge; Lighter/Darker; Optimize; Paper; Multi-page copy; Collation; Draft Mode; Image Adjustment; Set as
Seed 3.5 6 kbps fimanimum, 1.4.4 kbps (default) Memory (AP) Up to 1.300 pages Resolution Black (bette) Up to 300 x 300 dp Ballorinor). Black and White (Since): Up to 203 x 196 dp; Black Photo Grayscale Resolution Black (bette). Up to 300 x 300 dp; Ballorinor). Black and White (Since): Up to 203 x 196 dp; Black Photo Grayscale Resolution Autor Grant Carciton supported: Yes. Fast Refeating (Yes. Distinctive ring detection supported: Yes. Fast Refeating (Since): Yes. And Carciton (Yes. Fast Refeating). And The Carciton (Yes. Fast Refeating). Yes. Distinctive ring detection supported: Yes. Fast Refeating (Since): Yes. And Carciton (Yes. Fast Refeating). And The Carciton (Yes. Fast Speed disling) (max numbers): Up to 120 numbers. Fast phone TAM Interface supported: Yes. Fast Speed disling (max numbers): Up to 120 numbers. Fast phone TAM Interface supported: Yes. Fast Speed disling (max numbers): Up to 120 numbers. Fast phone TAM Interface supported: Yes. Past Speed disling (max numbers): Up to 120 numbers. Fast phone TAM Interface supported: Yes. Past Speed disling (max numbers): Up to 120 numbers. Fast phone TAM Interface supported: Yes. Past Speed disling (max numbers): Up to 120 numbers. Fast phone TAM Interface supported: Yes. Past Phone TAM Interface Speed disling (max numbers): Up to 120 numbers. Fast phone TAM Interface supported: Yes. Vest Phone TAM Interface Speed disling (max numbers): Up to 120 numbers. Fast phone TAM Interface Speed	Copier smart software features	Up to 99 multiple copies, Reduce/Enlarge from 25 to 400%, Fit to page, Customizable copy presets (two or four pages to one page),
Speed 33.6 kbps (maximum): 14.4 kbps (default)	Fax	contrast (tighter/darker), io copy, optimize copy selection (with presets, autoselect, mixed, printed picture, text)
Black Deets): Up to 300 x 300 dpt Black Exanderized 201 x 300 dpt Black Family Black And White Example 10; to 300 x 300 dpt Black Photo Grayscale 300 x 30	Speed	
Solve 300 de jún Michael, Black and White Superfine's Up is 300 x 300 de jún Michael Service (S. Auto Facet Vers, Auto Facet		
Fax forwarding supported: Ves, Sub harrier supported: Ves, Sub matching only (Galler ID not supported). Par interface supported: Ves Residence mode supported: Ves, Sub-good dailing intax numbers: But pilot 20 minumbers: A part plant interface supported: Ves Residence of Vesting and Part of Vesting Codes, poli receiver, fax activity reports, dial prefix setting. Smart software features Fax floodinating, Max Locations: 11 providing, TMA letter fixe, distinctive ring detection, cover page wizard (Software only), block fax belling to codes, poli receiver, fax activity reports, dial prefix setting. 2-line LCD with 26 buttors (0-9 digitals). Star Pound, Left, Right, LGK, Cancell, Back, Main Setup, wireless, Colour copy, Mono copy, Cop amount, Dankfajht, Copy setup. Start Fax, Redial) and 3 indicator light (Ready, Error, Wireless). 150 to 1,500 pages 150 t		300 x 300 dpi (halftone); Black and White (superfine): Up to 300 x 300 dpi
Simple Software features Autor redailing, delayed sending, fax forwarding, TAM interface, distinctive ring detection, cover page wizard (Software only), block fax billing codes, polit receive, fax activity reports, daily prefix setting Post Control panel 2-line LED with 26 buttons (0-9 digitals, Star Pound, Left, Right, OK, Cancel, Back, Main Setup, wireless, Colour copy, Mono copy, Cop amount, Darkhjight, Copy setup, Start Fax, Redail and 3 indicator light (Ready, Error, Wireless) 150 to 1,500 pages agree volume* 150 to 1,500 pages 15	Features	Fax forwarding supported: Yes; Junk barrier supported: Yes, CSID matching only (Caller ID not supported); PC interface supported: Ye Fax telephone mode supported: Yes; Fax speed dialing (max numbers): Up to 120 numbers; Fax phone TAM interface supported: Ye
Display 2-Line LCD Control panel 2-line LCD with 26 buttons (0-9 digitals, Star, Pound, Left, Right, CK, Cancel, Back, Main Setup, wireless, Colour copy, Mono copy, Cop amount, Darklight, Copy setup, Start Fax, Redail and 3 indicator light (Ready, Error, Wireless)	Smart software features	Auto redialing, delayed sending, fax forwarding, TAM interface, distinctive ring detection, cover page wizard (Software only), block fax,
amount, Darklight, Copy setup, Start Fax, Redail and 3 indicator light (Ready, Error, Wireless) 150 to 1,500 pages age volume* 150 to 1,500 pages age volume* 160 to 1,500 pages age volume* 170 to 1,500 pages 170 to 1,5	Display Control panel	2-Line LCD
Recommended monthly assign volume* Connectivity (Standard) Network capabilities Vex. via built-in 10/100 Base-TX Ethernet 10/100 Base-TX network port, 802.11 in 2.4/56Hz wireless, Fax port Network capabilities Vex. via built-in 10/100 Base-TX Ethernet authentication via 802.11 is Vex. via built-in 10/100 Base-TX Ethernet authentication via 802.11 is Wireless capability He Perint Apple Air Print** Mobile printing capability He Perint Apple Air Print** Hobile printing capability He Perint Apple Air Print** Hobile Air Print** H		amount, Dark/light, Copy setup, Start Fax, Redial) and 3 indicator light (Ready, Error, Wireless)
Connectivity Standard Hi-Speed USB 2.0 port; built-in Fast Ethernet 10/100 Base-TX network port, 80:2.11 n.2.4/5GHz wireless, Fax port	Recommended monthly	
Hi-Speed LGSE 2.0 port: bull-in Fast Ethernet. 10/10.0 Base-TX Network port, 802.1 In 2.4/5GHz wireless, Fax port Network capabilities Wireless capability Bull-in 10/10.0 Base-1X Network and the substitution with 802.1 In X-wireless capability Bull-in 10/10.0 Base-1X Ethernet. authentication via 802.1 In X-wireless capability He Pehrint, Apple AirPrint*, Mobile printing capability He Pehrint, Apple AirPrint*, Mobile Apps. Mopria* Certified. Wi-FP Dread Printing Movement of the Pehrint, Apple AirPrint*, Mobile Apps. Mopria* Certified. Wi-FP Dread Printing Movement of the Pehrint, Apple AirPrint*, Mobile Apps. Mopria* Certified. Wi-FP Dread Printing Movement of the Pehrint, Apple AirPrint*, Mobile Apps. Mopria* Certified. Wi-FP Dread Printing Movement of the Pehrint Apple AirPrint*, Mobile Apps. Mopria* Certified. Wi-FP Dread Printing Discovery. SLR Bonjour, Web Services Discovery. IP Config. In Vel Booth (Policy Audit) Movement of the Pehrint Apple Air Printing Discovery. SLR Bonjour, Web Services Discovery. IP Config. In Vel Booth (Policy Audit) Movement of the Pehrint Apple Air Printing Discovery. SLR Bonjour, Movement of the Pehront Apple Air Printing Discovery. SLR Bonjour, Movement of the Pehront Apple Air Printing Discovery. SLR Bonjour, Movement of the Pehront Air Printing Discovery. SLR Bonjour, Movement of the Pehront Air Printing Discovery. SLR Bonjour, Movement Discovery. SLR		
Sull-in-Big 2.1 to Egiff, authentication via WEB, WPAH/WPAZ, or 80.2.1 1x, encryption via AES or TXIP; WPS; Wi-Fi Direct Mobile Apps; Suprish (Certified; Wi-Fife Direct Printing Type) (Person Printing Type) (Person Printing) (Hi-Speed USB 2.0 port; built-in Fast Ethernet 10/100 Base-TX network port, 802.11n 2.4/5GHz wireless, Fax port
Media		
CEMPIE Plack, Pinkt: TEMPIE Plack Book Pinkt: TEMPIE Plack Book Delica was quasue support only), Web Services Printing: Discovery: SLP, Bonjour, Web Services Discovery: IP Config: IPv4 (Book Delica was quasue support only), Web Services Printing: Discovery: SLP, Bonjour, Web Services Discovery: IP Config: IPv4 (Book Delica was previous).		
Paper handling Input: 150-sheet input tray; Output: 100-sheet output bin Paper (bond, brochure, coloured, glossy, heavy, letterhead, light, photo, plain, preprinted, prepunched, recycled, rough), transparenciables, envelopes, cardstock Weight (Supported) 60 to 163 gm² (Costed/Glossy, recommended), however up to 175 g/m² Postcards and 200 g/m² HP Matte is allowed in the driver, to 163 gm² (Costed/Glossy, recommended), however up to 175 g/m² Postcards and 220 g/m² HP Glossy is allowed in the driver, to 163 gm² (Costed/Glossy, recommended), however up to 175 g/m² Postcards and 220 g/m² HP Glossy is allowed in the driver, to 163 g/m² (Costed/Glossy, recommended), however up to 175 g/m² Postcards and 220 g/m² HP Glossy is allowed in the driver, to 163 g/m² (Costed/Glossy, recommended), however up to 175 g/m² Postcards and 220 g/m² HP Glossy is allowed in the driver, to 163 g/m² (Costed/Glossy), and 164 g/m² (Costed/Glossy), and		TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Web Services Printing; Discovery: SLP, Bonjour,
Paper (bond, brochure, coloured, glossy, heavy, letterhead, light, photo, plain, preprinted, prepunched, recycled, rough), transparency labels, envelopes; cardstock Weight (Supported) 60 to 163 g/m² (Unicoated/Matte, recommended), however up to 175 g/m² Postcards and 200 g/m² HP Matte is allowed in the driver. Sizes (Supported) Extert(216 x 280), Legal(216 x 356), Executive(184 x 267), 0ftiol 8.5xi 3(216 x 330), 4 x (6102 x 152), 5 x 8(127 x 203), A4(210 x 299), A5(148 x 10), A6(105x148), B5(15)(182 x 257), B6(15)(128 x 182), 10x1 scm(100x15), 0ftiol 2 fex340mm(2 fex 340), 161 ps. 270, 161 ps	Media	
Labels, envelopes, cardstock		
Sizes (Supported) 60 to 163 g/m² (Uncoated/Matte, recommended), however up to 175 g/m² Postcards and 200 g/m² IP Matte is allowed in the driver, to 163 g/m² (Coated/Glossy, recommended), however up to 175 g/m² Postcards and 220 g/m² IP Glossy is allowed in the driver, to 163 g/m² (Coated/Glossy, recommended), however up to 175 g/m² Postcards and 220 g/m² IP Glossy is allowed in the driver, to 163 g/m² (Coated/Glossy, recommended), however up to 175 g/m² Postcard 220 g/m² IP Glossy is allowed in the driver, 299); A5 (148 x 210); A6 (105x 148); B5(IS)(182 x 257); B6(IS)(128 x 182); 10x 15cm (100 x 150); Ofico 216x 340mm (216 x 340); 16 (195x 270mm) (195x 270	Type	
Letter(216 x 280); Legal(216 x 356); Executive(184 x 267); Ofticia B.Sxi1(216 x 330); 4x (102 x 152); 5x (127 x 203); A4(210 x 293); A5(148 x 210); A5(1054 x 184); BSUIS(116) (128 x 257); BS(107) (128 x 182); 105 (105 x 153); A5(102 x 152); 105 (128 x 120); 1	Weight (Supported)	60 to 163 g/m2 (Uncoated/Matte, recommended), however up to 175 g/m2 Postcards and 200 g/m2 HP Matte is allowed in the driver;
195x270mm(195x270l); 16K 184x260mm(184x260); 16K 197x273lmm(197x273); Postcard(JIS)(10 x 147); Double Postcard(JIS)(1 x 200); Envelope #10(105 x 241); Envelope Monarch(98 x 191); Envelope BS(176 x 250); Envelope CS(162 x 229); Envelope DL(110: 220); AS-R(210 x 148) Processor speed 800 MHz Standard/Maximum: 256 MB DDR, 128 MB Flash Windows* 10, 8.1, 8, 7: 32-bit or 64-bit, 2 GB available hard disk space, Internet connection, USB port, Internet Explorer 8. Windows* XPSP3 or higher (32-bit only): any Intel* Pentium* II, Celeron* or 233 MHz compatible processor, 850 MB available hard disk space, Internet connection, USB port, Internet Explorer 8. Windows* XPSP3 or higher (32-bit only): any Intel* Pentium* II, Celeron* or 233 MHz compatible processor, 850 MB available hard disk space, Internet connection, USB port, Internet Explorer 8. Windows* Server support is provided via the command line installer and supports Win Server 2008 R2 a higher. Apple* macOS Siera (10.12) macOS highs Fiser (10.13) macOS highave (10.14) macOS Catalinar(10.15); 200MB Hp; Internet requirements PC: Windows* 10, 8.1, 8, 7: 32-bit or 64-bit, 2 GB available hard disk space, Internet connection, USB port, Internet Explorer 8. Windows Wista* (32-bit only); any Intel* Pentium* II, Celeron* or 233 MHz compatible processor, 850 MB available hard disk space, Internet connection, USB port, Internet Explorer 8. Windows* Server support is provided via the command line installer and supports Win Server 2008 R2 a higher. Mac. Apple* macOS Siera (10.12) macOS High Siera (v10.13) macOS Mojave (v10.14) macOS Catalinal(v10.15); 200MB HD; Internet required for download; USB Dimensions (W x D x H)* Weight* 16.3 kg Dimensions (W x D x H)* Operating environment Operating temperature range: 10 to 32.5°C; Recommended operating temperature: 15 to 27°C; Operating humidity range: 10 to 80% RH; Recommended operating humidity range: 30 to 70% RH; Non-operating Humidity Range: 0 to 95% RH; Storage temperature range: 20 to 40°C. Acoustic power emissions bysta	Sizes (Supported)	Letter(216 x 280); Legal(216 x 356); Executive(184 x 267); Oficio 8.5x13(216 x 330); 4 x 6(102 x 152); 5 x 8(127 x 203); A4(210 x
Processor speed 800 MHz Sandard/Maximum: 256 MB DDR, 128 MB Flash Windows® 10, 8.1, 8, 7: 32-bit or 64-bit, 2 GB available hard disk space, Internet connection, USB port, Internet Explorer 8. Windows® XP SP3 or higher (32-bit only); 2 GB available hard disk space, Internet connection, USB port, Internet Explorer 8. Windows Sex (32-bit only); 2 GB available hard disk space, Internet connection, USB port, Internet Explorer 8. Windows Sex (32-bit only); 2 GB available hard disk space, Internet connection, USB port, Internet Explorer 8. Windows Sex provided via the command line installer and supports Win Server 2008 R.2 a higher. Apple® macOS Sierra (v10.12) macOS High Sierra (v10.13) macOS Mojave (v10.14) macOS Catalina(v10.15); 200MB HD; Internet explorer 8. Windows Sex very support is provided via the connection, USB port, Internet Explorer 8. Windows Sex very support is provided via the connection, USB port, Internet Explorer 8. Windows Sex very support is provided via the connection, USB port, Internet Explorer 8. Windows Sex very support is provided via the command line installer and supports Win Sex via 25-bit only); 2 GB available hard disk space, Internet connection. USB port, Internet Explorer 8. Windows Sex very support is provided via the command line installer and supports Win Sex via 25-bit only); 2 GB available hard disk space, Internet connection. USB port, Internet Explorer 8. Windows Sex very support is provided via the command line installer and supports Win Sex via 15-bit only 2 GB available hard disk space, Internet connection. USB port, Internet Explorer 8. Windows Sex very support is provided via the command line installer and supports Win Sex via 15-bit only 2 GB available hard disk space, Internet connection. USB port, Internet Explorer 8. Windows Sex very support is provided via the command line installer and supports Win Sex via 15-bit only 2 GB available hard disk space, Internet connection. USB port, Internet Explorer 8. Windows Sex very support is provided via the command line instal		299); A5(148 x 210); A6(105x148); B5(JIS)(182 x 257); B6(JIS)(128 x 182); 10x15cm(100 x 150); Oficio 216x340mm(216 x 340); 16K 195x270mm(195x270); 16K 184x250mm(195x273); Postcard(JIS)(1100 x 147); Double Postcard(JIS)(110 x 270); Postcard(JIS)(110 x 147); Double Postcard(JIS)(JIS)(110 x 147); Double Postcard(JIS)(JIS)(JIS)(JIS)(JIS)(JIS)(JIS)(JIS)
Standard/Maximum: 256 MB DDR, 128 MB Flash	D	220); A5-R(210×148)
Operating system compatibility	Processor speed Memory	
(32-bit only): any Intel® Pentium® II, Celeron® or 23 MHz compatible processor, 850 MB available hard disk space, Internet Connection USB port, Internet Explorer B. Windows Server support is provided wit are town mand line installer and supports Win Server 2008 R2 a higher Apple® macOS Sierra (v10.12) macOS High Sierra (v10.13) macOS Mojave (v10.14) macOS Catalina(v10.15); 200MB HD; Internet requirered for download; USB. Linux (For more information, see developers.hp.com/hp-linux-imaging-and-printing). Unix (For more information, see hp.com) PC: Windows® 10, 8.1, 8, 7: 32-bit or 64-bit, 2 GB available hard disk space, Internet connection, USB port, Internet Explorer 8. Windows® XP SP3 or higher (32-bit only); any Intel® Pentium® II, Celeron® or 233 MHz compatible processor, 850 MB available hard disk space, Internet connection, USB port, Internet Explorer 8. Windows® XP SP3 or higher (32-bit only); any Intel® Pentium® II, Celeron® or 233 MHz compatible processor, 850 MB available hard disk space, Internet connection. USB port, Internet Explorer 8. Windows Server support is provided via the command line installer and supports Win Server 2008 R2 a higher. Mac: Apple® macOS Siera (v10.12) macOS High Sierra (v10.13) macOS Mojave (v10.14) macOS Catalina(v10.15); 200MB HD; Internet required for download; USB Dimensions (W x D x H)® Weight* 16.3 kg Environmenta Operating environment Operating temperature range: 10 to 32.5°C; Recommended operating temperature: 15 to 27°C; Operating humidity range: 10 to 80% RH; Recommended operating humidity range: 30 to 70% RH; Non-operating Humidity Range: 0 to 95% RH; Storage temperature range: 20 to 40°C. Acoustics Acoustic power emissions (active, printing): 6.2 B(A) (Mono); 6.3 B(A) (Colour); Acoustic power emissions bystander (active sca 45 dB(A) (Mono); 4.2 dB(A) (Colour); Acoustic pressure emissions bystander (active sca 45 dB(A) (Mono); 4.2 dB(A) (Colour); Acoustic pressure emissions bystander (active sca 45 dB(A) (Mono); 4.2 dB(A) (Colour); Acoustic pressure emissio	Operating system compatibility	Windows® 10, 8.1, 8, 7: 32-bit or 64-bit, 2 GB available hard disk space, Internet connection, USB port, Internet Explorer. Windows
higher. Apple® macOS. Sierra (v10.12) macOS High Sierra (v10.13) macOS Mojave (v10.14) macOS Catalina(v10.15); 200MB HD; Interrr required for download; USE. Linux (For more information, see developers.hp.com/hp-linux-imaging-and-printing). Unix (For more information, see hp.com) PC: Windows® 10, 8.1, 8, 7:32-bit or 64-bit; 2 GB available hard disk space, Internet connection, USB port, Internet Explorer. 8. Windows® Nos Space on Higher (32-bit only), 2 GB available hard disk space, Internet connection, USB port, Internet Explorer 8. Windows® Nos Space on Higher (32-bit only), 2 GB available hard disk space, Internet connection, USB port, Internet Explorer 8. Windows® Nos Space on Higher (32-bit only), 2 GB available hard disk space, Internet explorer 9. Windows® Nos Space on Higher (32-bit only), 2 GB available hard disk space, Internet explorer 9. Windows® Nos Space on Higher (32-bit only), 2 GB available hard disk space, Internet explorer 9. Windows® Nos Space on Higher (32-bit only), 2 GB available hard disk space, Internet explorer 9. Windows® Nos Space on Higher (32-bit only), 2 GB available hard disk space, Internet explorer 6. Windows® Nos Space on Higher (32-bit only), 2 GB available hard disk space, Internet explorer 6. Windows® Nos Space (10-12) MacOS Mojave (v10.14) macOS Catalina(v10.15); 200MB HD; Internet explorer 8. Windows Space (v10.12) macOS High Space (v10.13) macOS Mojave (v10.14) macOS Catalina(v10.15); 200MB HD; Internet explorer 6. Windows Min Space (v10.14) macOS Available hard disk space, Internet Explorer 9. Win Space (v10.14) macOS Available hard disk space, Internet Explorer 9. Win Space (v10.14) macOS Available hard disk space, Internet Explorer 8. Win Space (v10.14) macOS Available hard disk space, Internet Explorer 8. Win Space (v10.14) macOS Available hard disk space, Internet Explorer 8. Win Space (v10.14) macOS Available hard disk space, Internet Explorer 8. Win Space (v10.14) macOS Available hard disk space, Internet Explorer 9. Win Space (v10.14) macOS Available hard disk spa		(32-bit only): any Intel® Pentium® II, Celeron® or 233 MHz compatible processor, 850 MB available hard disk space, Internet connection
Minimum system requirements PC: Windows® 10, 8.1, 8, 7: 32-bit or 64-bit, 2 GB available hard disk space, Internet connection, USB port, Internet Explorer. Windows® XP SP3 or higher (32-bit only), 2 GB available hard disk space, Internet connection, USB port, Internet Explorer 8. Windows® XP SP3 or higher (32-bit only); any Intel® Pentium® II, Celeron® or 233 MHz compatible processor, 89.0 MB available hard disk space, Internet Connection USB port, Internet Explorer 8. Windows Server support is provided via the companion of the win Server 2008 R2 a higher. Mac: Apple® macOS Sierra (v10.12) macOS High Sierra (v10.13) macOS Mojave (v10.14) macOS Catalina(v10.15); 200MB HD; Internet required for download; USB ### 420 x 380 x 341.2 mm ### 16.3 kg ### 16.3 kg ### Operating temperature range: 10 to 32.5°C; Recommended operating temperature: 15 to 27°C; Operating humidity range: 10 to 80% RH; Recommended operating humidity range: 30 to 70% RH; Non-operating humidity Range: 0 to 95% RH; Storage temperature range: 20 to 40°C. ### Storage temperature range: 20 to 40°C. ### Acoustics ### Acoustic power emissions (active, printing): 6.2 B(A) (Mono); 6.3 B(A) (Colour); Acoustic power emissions bystander (ready): 16 d8 (A); Acoustic power emissions (active scan): 6.0 B(A) (Mono); 5.4 B(A) (Colour); Acoustic pressure emissions bystander (ready): 16 d8 (A); Acoustic power emissions (active scan): 6.0 B(A) (Mono); 5.4 B(A) (Colour); Acoustic pressure emissions bystander (ready): 16 d8 (A); Acoustic power emissions (active scan): 6.0 B(A) (Mono); 5.4 B(A) (Colour); Acoustic pressure emissions bystander (ready): 16 d8 (A); Acoustic power emissions (active scan): 6.0 B(A) (Mono); 5.4 B(A) (Colour); Acoustic pressure emissions bystander (ready): 16 d8 (A); Acoustic power emissions (active scan): 6.0 B(A) (Mono); 5.4 B(A) (Colour); Acoustic pressure emissions bystander (ready): 16 d8 (A); Acoustic power emissions (active scan): 6.0 B(A) (Mono); 6.3 B(A) (Colour); Acoustic pressure emissions bystander (ready): 16 d8 (A); Acous		higher. Apple® macOS Sierra (v10.12) macOS High Sierra (v10.13) macOS Mojave (v10.14) macOS Catalina(v10.15); 200MB HD; Internet
Wista ⁶ : (32-bit only), 2 GB available hard disk space, Internet connection, USB port, Internet Explorer 8. Windows* XP SP3 or higher (32-bit only); any Intel® Pertitum® II, Celerom® or 23 MHz compatible process, SB0 MB available hard disk space, Internet connectic USB port, Internet Explorer 8. Windows Server support is provided via the command line installer and supports Win Server 2008 R2 a higher Mac. Apple® mac05 Sierra (v10.12) mac05 High Sierra (v10.13) mac05 Mojave (v10.14) mac05 Catalina(v10.15); 200MB HD; Internet required for download; USB Dimensions (W x D x H) ^a 420 x 380 x 341.2 mm 420 perating environment Operating environment Operating environment Operating environment Operating temperature range: 10 to 32.5°C; Recommended operating temperature: 15 to 27°C; Operating humidity range: 10 to 80% RH; Recommended operating humidity range: 30 to 70% RH; Non-operating humidity Range: 0 to 95% RH; Storage temperature range: 20 to 40° C Acoustic ower emissions (active, printing); 6.2 B(A) (Mono); 6.3 B(A) (Colour); Acoustic power emissions (ready); 2.6 B(A); Acoustic pressure emissions bystander (active, printing); 4.8 dB(A)(Mono); 4.9 dB(A) (Colour); Acoustic pressure emissions bystander (active scales of 80 Mono); 5.4 BIA (Nono); 5.0 Hz (-/- 3 Hz), 60 Hz (-/- 3 Hz); 62 Dz-volt input voltage; 220 to 240 VX (-/- 10%), 50 Hz (-/- 3 Hz), 60 Hz (-/- 3 Hz); 62 Dz-volt input voltage; 220 to 240 VX (-/- 10%), 50 Hz (-/- 3 Hz), 60 Hz (-/- 3 Hz); 62 Dz-volt input voltage; 220 to 240 VX (-/- 10%), 50 Hz (-/- 3 Hz), 60 Hz (-/- 3 Hz); 62 Dz-volt input voltage; 220 to 240 VX (-/- 10%), 50 Hz (-/- 3 Hz), 60 Hz (-/- 3 Hz); 62 Dz-volt input voltage; 220 to 240 VX (-/- 10%), 50 Hz (-/- 3 Hz), 60 Hz (-/- 3 Hz); 62 Dz-volt input voltage; 220 to 240 VX (-/- 10%), 50 Hz (-/- 3 Hz), 60 Hz (-/- 3 Hz); 62 Dz-volt input voltage; 220 to 240 VX (-/- 10%), 50 Hz (-/- 3 H		information, see <u>hp.com</u>)
(32-bit only): any Intel® Pentium® II, Celeron® or 233 MHz compatible processor, 850 MB available hard disk space, Internet Connection USB port, Internet Explorer & Windows Server support is provided via the companion of the internet explorer is provided via the companion of the internet required for download; USB Internet required for download; USB Olimensions (W x D x H)® Weight* 16.3 kg Environmental Operating environment Operating environment Operating environment Operating temperature range: 10 to 32.5°C; Recommended operating temperature: 15 to 27°C; Operating humidity range: 10 to 80% RH; Recommended operating humidity range: 30 to 70% RH; Non-operating Humidity Range: 0 to 95% RH; Storage temperature range: 20 to 40°C Acoustics Acoustic power emissions (active, printing): 6.2 B(A) (Mono); 6.3 B(A) (Colour); Acoustic power emissions (ready): 2.6 B(A) (Acoustic power emissions bystander (active scan): 6.0 B(A) (Mono); 5.4 B(A) (Colour); Acoustic power emissions bystander (ready): 4.5 B(A) (Mono); 5.4 B(A) (Colour); Acoustic pressure emissions bystander (ready): 4.5 B(A) (Mono); 5.4 B(A) (Colour); Acoustic pressure emissions bystander (active scan): 6.0 B(A) (Mono); 5.4 B(A) (Colour); Acoustic pressure emissions bystander (active scan): 6.0 B(A) (Mono); 5.4 B(A) (Colour); Acoustic pressure emissions bystander (ready): 4.5 B(A) (Mono); 4.2 B(A) (Colour); Acoustic pressure emissions bystander (active scan): 6.0 B(A) (Mono); 5.4 B(A) (Colour); Acoustic pressure emissions bystander (active scan): 6.0 B(A) (Mono); 7.4 B(A) (Colour); Acoustic pressure emissions bystander (active scan): 6.0 B(A) (Mono); 7.4 B(A) (Colour); Acoustic pressure emissions bystander (active scan): 6.0 B(A) (Mono); 7.4 B(A) (Colour); Acoustic pressure emissions bystander (active scan): 6.0 B(A) (Mono); 7.4 B(A) (Colour); Acoustic pressure emissions bystander (active scan): 6.0 B(A) (Mono); 7.4 B(A) (Colour); Acoustic pressure emissions bystander (active scan): 6.0 B(A) (Mono); 7.4 B(A) (Colour); Acoustic pressure emissions bystan	Minimum system requirements	PC: Windows® 10, 8.1, 8, 7: 32-bit or 64-bit, 2 GB available hard disk space, Internet connection, USB port, Internet Explorer. Windows Vista®: (32-bit only), 2 GB available hard disk space, Internet connection, USB port, Internet Explorer 8. Windows® XP SP3 or higher
higher, Mac: Apple® macOS Sierra (v10.12) macOS High Sierra (v10.13) macOS Mojave (v10.14) macOS Catalina(v10.15); 200MB HD; Internet required for download; USB Weight* 16.3 kg Dimensions (W x D x H)® 16.3 kg Derating environment Operating temperature range: 10 to 32.5°C; Recommended operating temperature: 15 to 27°C; Operating humidity range: 10 to 80% RH; Recommended operating humidity range: 30 to 70% RH; Non-operating humidity Range: 0 to 95% RH; Storage temperature range: 20 to 40°C. Acoustics Acoustic power emissions (active, printing): 6.2 B(A) (Mono): 6.3 B(A) (Colour); Acoustic power emissions (ready): 2.6 B(A); Acoustic pressure emissions bystander (ready): 16 dk (A); Acoustic power emissions (active scan): 6.0 B(A) (Mono): 5.4 B(A) (Colour); Acoustic pressure emissions bystander (ready): 16 dk (A); Acoustic power emissions (active scan): 6.0 B(A) (Mono): 5.4 B(A) (Colour); Acoustic pressure emissions bystander (ready): 16 dk (A); Acoustic power emissions (active scan): 6.0 B(A) (Mono): 5.4 B(A) (Colour); Acoustic pressure emissions bystander (ready): 16 dk (A); Acoustic power emissions (active scan): 6.0 B(A) (Mono): 5.4 B(A) (Colour); Acoustic pressure emissions bystander (ready): 16 dk (A); Acoustic power emissions (active scan): 6.0 B(A) (Mono): 5.4 B(A) (Colour); Acoustic pressure emissions bystander (ready): 16 dk (A); Acoustic power emissions (active scan): 6.0 B(A) (Mono): 5.4 B(A) (Colour); Acoustic pressure emissions bystander (ready): 16 dk (A); Acoustic power emissions (active scan): 6.0 B(A) (Mono): 5.4 B(A) (Colour); Acoustic pressure emissions bystander (ready): 16 dk (A); Acoustic pressure emissions bystander (ready): 16 dk (A); Acoustic power emissions (active scan): 6.0 B(A) (Mono): 5.4 B(A) (Colour); Acoustic pressure emissions bystander (ready): 16 dk (A); Acoustic power emissions (active scan): 6.0 B(A) (Mono): 5.4 B(A) (Colour); Acoustic power emissions (ready): 16 dk (A); Acoustic power emissions (active scan): 6.0 B(A) (Mono): 6.3 B(A) (Mono): 6.3 B(A) (Mono): 6.3 B(A)		(32-bit only): any Intel® Pentium® II, Celeron® or 233 MHz compatible processor, 850 MB available hard disk space, Internet connection
Acoustics Acoustic power emissions (active, printing): 4.20 km/s (2.6 km/s); Recommended operating temperature: 15 to 27°C; Operating humidity range: 10 to 32.5°C; Recommended operating temperature: 15 to 27°C; Operating humidity range: 10 to 80% RH; Recommended operating humidity range: 30 to 70% RH; Non-operating humidity Range: 0 to 95% RH; Storage temperature range: -20 to 40°C Acoustic power emissions (active, printing): 6.2 B(A) (Mono); 6.3 B(A) (Colour); Acoustic power emissions (ready): 2.6 B(A); Acoustic pressure emissions bystander (ready): 16 dB (A); Acoustic power emissions (active scan): 6.0 B(A) (Mono); 5.4 B(A) (Colour); Acoustic pressure emissions bystander (ready): 16 dB (A); Acoustic power emissions (active scan): 6.0 B(A) (Mono); 5.4 B(A) (Colour); Acoustic pressure emissions bystander (ready): 16 dB (A); Acoustic power emissions (active scan): 6.0 B(A) (Mono); 5.4 B(A) (Colour); Acoustic pressure emissions bystander (ready): 16 dB (A); Acoustic power emissions (active scan): 6.0 B(A) (Mono); 5.4 B(A) (Colour); Acoustic pressure emissions bystander (ready): 16 dB (A); Acoustic power emissions bystander (ready): 16 dB (A); Acoustic power emissions (active scan): 6.0 B(A) (Mono); 5.4 B(A) (Colour); Acoustic pressure emissions bystander (ready): 16 dB (A); Acoustic power emissions bystander (ready): 16 dB (A); Acoustic pressure emissions bystander (ready): 16 dB (A); Acoustic power emissions bystander (ready): 16 dB (A); Acoustic pressure emissions bystander (ready): 16 dB (A); Acoustic power em		higher. Mac: Apple® macOS Sierra (v10.12) macOS High Sierra (v10.13) macOS Mojave (v10.14) macOS Catalina(v10.15); 200MB HD;
Meight* 16.3 kg	Dimensions (W x D x H) ⁸	
Operating environment Operating temperature range: 10 to 32.5°C, Recommended operating temperature: 15 to 27°C, Operating humidity range: 10 to 80% RH; Recommended operating humidity range: 20 to 70% RH; Non-operating humidity Range: 0 to 95% RH; Storage temperature range: -20 to 40°C Acoustics Acoustic power emissions (active, printing): 6.2 B(A) (Mono); 6.3 B(A) (Colour); Acoustic power emissions (ready): 2.6 B(A); Acoustic pressure emissions bystander (ready): 16 dB (A); Acoustic power emissions (active scan): 6.0 B(A) (Mono); 5.4 B(A) (Colour); Acoustic pressure emissions bystander (ready): 16 dB (A); Acoustic power emissions (active scan): 6.0 B(A) (Mono); 5.4 B(A) (Colour); Acoustic pressure emissions bystander (ready): 6.5 dB (A) (Mono); 42 dB (A) (Mono); 42 dB (A) (Mono); 5.4 B(A) (Colour); Acoustic pressure emissions bystander (ready): 6.5 dB (A); Acoustic pressure emissions bystander (ready): 6.5 dB (A	Weight ⁹	
10 to 80% RH; Recommended operating humidity range: 30 to 70% RH; Non-operating Humidity Range: 0 to 95% RH; Storage temperature range: -20 to 40° C Acoustics Acoustic power emissions (active, printing): 6.2 B(A) (Mono); 6.3 B(A) (Colour); Acoustic power emissions (ready): 2.6 B(A); Acoustic pressure emissions bystander (active, printing); 48 dB(A) (Mono); 49 dB(A) (Colour); Acoustic power emissions bystander (active, printing): 48 dB(A) (Mono); 49 dB(A) (Colour); Acoustic power emissions bystander (active scales of the Mono); 5.4 B(A) (Mono); 6.0 dB(A) (Mono);		Operating temperature range: 10 to 32.5°C Recommended operating temperature: 15 to 27°C Operating humidity range:
Acoustics Acoustic power emissions (active, printing): 6.2 B(A) (Mono); 6.3 B(A) (Colour); Acoustic power emissions (ready); 2.6 B(A); Acoustic pressure emissions bystander (active, printing): 48 dB(A) (Mono); 4.9 dB(A) (Colour); Acoustic power emissions bystander (ready); 16 dB (A); Acoustic power emissions foative scan); 6.0 B(A) (Mono); 4.9 dB(A) (Colour); Acoustic pressure emissions bystander (active scan); 6.0 B(A) (Mono); 4.2 dB(A) (Colour); Acoustic pressure emissions bystander (active scan); 6.0 B(A) (Mono); 4.2 dB(A) (Colour); Acoustic pressure emissions bystander (active scan); 6.0 B(A) (Mono); 4.2 dB(A) (Colour); Acoustic pressure emissions bystander (active scan); 6.0 B(A) (Mono); 4.2 dB(A) (Colour); Acoustic pressure emissions bystander (active scan); 7.0 B(A) (Mono); 4.2 dB(A) (A) (A) (A) (A) (A) (A) (A) (A) (A)	-paramy cresoffilient	10 to 80% RH; Recommended operating humidity range: 30 to 70% RH; Non-operating Humidity Range: 0 to 95% RH;
Power supply type: Internal (Built-in) power supply; Power supply required: 110-volt input voltage: 110 to 127 VAC (+-1 10%), 50 Hz (+/-3 Hz), 60 Hz (+/-3 Hz), 70 Watts(Ready), 0.7 Watts(Sleep), 0.05 (Manual-0ft), 0.05(Auto-0ft/Manual-0n), 1.0 watts(Auto-0ft/Wake on LAN); Typical electricity consumption (TEC) ES: 0.203 kMy/Week; BA: 0.531 kWh/Week; BA: 0.531 kWh/Week	Acoustics	Acoustic power emissions (active, printing): 6.2 B(A) (Mono); 6.3 B(A) (Colour); Acoustic power emissions (ready): 2.6 B(A); Acoustic pressure emissions bystander (active, printing); 4.8 B(BA) (Mono); 4.9 B(BA) (Colour); Acoustic pressure emissions bystander (ready): 1.6 B(A); Acoustic power emissions (active scan): 6.0 B(A) (Mono); 5.4 B(A) (Colour); Acoustic pressure emissions bystander factive scan
Hz (4/- 3 Hz), 60 Hz (4/- 3 Hz), 202-oit input voltage: 220 to 240 Vd. (-4 - 10%), 50 Hz (4/- 3 Hz), 60 Hz (4/- 3 Hz)(Not dual voltage, product varies by part number with # 0 plain code identifier). Power consumption: 313 watts(active printing), 7.4 watts(Ready), 0.7 vatts(Sleep), 0.05 (Manual-Off), 0.05(Auto-Off/Manual-On), 1.0 watts(Auto-Off/Wake on LAN); Typical electricity consumption (TEC) ES: 0.203 kWh/Week; BA: 0.531 kWh/Week No CD (Software is not included In-Box); Downloadable Software only from hp.com, 123.hp.com/laserjet or 123.hp.com Warranty One-year unit exchange warranty. Warranty and support options vary by product, country and local legal requirements. Go to hp.com/support to learn about HP award winning service and support options in your region. What's in the box¹º HP Color LaserJet Pro MPP M183 fw (7kW56A); Introductory HP LaserJet Color cartridges (-700 colour composite (C/V/M) page yield a	Power specifications	
ES: 0.203 kWh/Week; BA: 0.531 kWh/Week No CD (Software is not included In-Box); Downloadable Software only from hp.com, 123.hp.com/laserjet or 123.hp.com Warranty One-year unit exchange warranty. Warranty and support options vary by product, country and local legal requirements. Go to hp.com/support to learn about HP award winning service and support options in your region. What's in the box¹º HP Color LaserJet Pro MFP M183fw (7KW56A); Introductory HP LaserJet Color cartridges (~700 colour composite (C/V/M) page yield a	specifications	Hz (+/- 3 Hz), 60 Hz (+/- 3 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50 Hz (+/- 3 Hz), 60 Hz (+/- 3 Hz) (Not dual voltage,
Warranty One-year unit exchange warranty. Warranty and support options vary by product, country and local legal requirements. Go to hp.com/support to learn about HP award winning service and support options in your region. What's in the box10 HP Color LaserJet Pro MFP M183fw (7KW56A); Introductory HP LaserJet Color cartridges (~700 colour composite (C/V/M) page yield a	C. ft	ES: 0.203 kWh/Week; BA: 0.531 kWh/Week
hp.com/support to learn about HP award winning service and support options in your region. What's in the box¹o HP Color Laser Jet Pro MFP M183fw (7KW56A); Introductory HP Laser Jet Color cartridges (~700 colour composite (C/V/M) page yield a		
What's in the box10 HP Color LaserJet Pro MFP M183fw (7KW56A); Introductory HP LaserJet Color cartridges (~700 colour composite (C/Y/M) page yield a	wandiity	
	What's in the hov10	HP Color LaserJet Pro MFP M183fw (7KW56A); Introductory HP LaserJet Color cartridges (~700 colour composite (C/Y/M) page yield at

Ordering information

Description

7KW56A	HP Color LaserJet Pro MFP M183fw			
Replacement Cartridges and LLC's ¹¹				
Number	Description			
W2310A	HP 215A Black LaserJet Toner Cartridge (~1,050 yield)			
W2311A	HP 215A Cyan LaserJet Toner Cartridge (~850 yield)			
W2312A	HP 215A Yellow LaserJet Toner Cartridge (~850 yield)			
W2313A	HD 2154 Magenta Lacer Let Toner Cartridge (~850 yield)			

HP Care Packs

Number	Description
Nullibei	Description
UH757E	HP 3-year Next Business Day Consumer LaserJet
	MFP - E SVC
UH764E	HP 3-year Return Consumer LaserJet MFP - E SVC
UH769E	HP 3-year Pickup Return Consumer LaserJet MFP -E SV
UH773E	HP 3-year Onsite Exchange Consumer LaserJet MFP
	ECVIC

Protect your investment with HP Care Pack. Let HP certified engineers resolve your technical issues. For more details on HP Care Pack, go to hp.com/go/cpc

HP Inc offices

Australia	(613) 8833 5000	hp.com.au
Hong Kong	(852) 3077 2688	hp.com.hk
India	(80) 2612 9000	hp.com/in
Indonesia	(62-21) 5799 1088	hp.com/id
Korea	82 2-1544-0134	hp.co.kr
Malaysia	(603) 2332 3333	hp.com.my
Philippines	(632) 888 5900	hp.com/ph
Singapore	(65) 6275 3888	hp.com.sg
Taiwan	(02) 8722 9000	hp.com.tw
Thailand	(662) 353 9500	hp.com/th
Vietnam	(848) 3823 4151	hp.com/vn

HP Order-a-Cartridge

Call HP's Order-a-Cartridge12 service and have them conveniently delivered to your doorstep.

1800 3003 3003 India

Recommended Papers¹²

Number	Description
CG964A	HP Professional Laser Paper, Glossy, A4, 250 sheets,
	120 gsm
CG965A	HP Professional Laser Paper, Glossy, A4, 150 sheets, 150 gsm
CG966A	HP Professional Laser Photo Paper, Glossy, A4, 100 sheets, 200 gsm
Q6550A	HP Professional Laser Photo Paper, Matte, A4, 100 sheets

Please visit hp.com/apac/paper for more details.

HP Web Jetadmin: hp.com/go/wja HP Universal Print Driver: hp.com/go/upd HP JetAdvantage Security Manager: hp.com/go/securitymanager To Learn more about available infrastructure, management, and workflow solutions, visit hp.com/go/gsc











© Copyright 2019 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein

