



## MS823dn

Reliability. Security. Productivity.



This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

# Lexmark MS823dn

The Lexmark MS823dn brings performance to its class with a first page as fast as 4.2 seconds, output up to 61 pages per minute\*, and two-sided printing. Robust paper handling technology is designed to make printing more reliable, while optional finishing adds useful capabilities and thoughtful engineering enhances serviceability.



## Get more done

- ▶ Powerful 1-GHz dual-core processor and up to 4.5 GB of memory drives printing at up to 61 ppm.\*
- ▶ Maximum input capacity of 4400 sheets means fewer interruptions.
- ▶ Connect via Ethernet, USB, or simple mobile printing options.

## Interact with ease

- ▶ 6-cm colour LCD lets you configure, interact and monitor vital system information.
- ▶ Front access to the paper path and power button means you'll virtually never have to access the back of the device, allowing placement in or on cabinets.
- ▶ Innovative serviceability features, starting with single-door access to parts and supplies, help you resolve problems quickly.

## Ready when you are

- ▶ Long-life fuser and imaging components extend uptime.
- ▶ Unison™ Toner replacement cartridges deliver up to 55,000 pages\*\* of high-quality printing.
- ▶ Steel frame and durable design stands up to heavy use and harsh environments.

## Full-spectrum security

- ▶ Lexmark's full-spectrum security architecture helps keep your information safe—in the document, on the device and over the network.
- ▶ Keypoint Intelligence - Buyers Lab honoured Lexmark with a prestigious BLI PaceSetter award for Document Imaging Security\*\*\*.



## Built for planet earth


- ▶ Energy management features reduce power consumption in active use or sleep mode.
- ▶ Standard two-sided printing saves paper.
- ▶ Device is rated EPEAT® Silver and ENERGY STAR® certified.
- ▶ Recycle cartridges through the award-winning Lexmark Cartridge Collection Programme (LCCP).

\*Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: [www.lexmark.com/ISOspeeds](http://www.lexmark.com/ISOspeeds).

\*\*Average standard page yield value declared in accordance with ISO/IEC 19752.

\*\*\*Award based on North America and/or Western Europe data

# Lexmark MS823dn



- 1 Printer with 6 cm colour display  
445 x 428 x 510 mm
- 2 100-sheet multipurpose feeder  
Dimensions included as part of base model
- 3 550-sheet tray  
Dimensions included as part of base model
- 4 550-sheet tray 110 x 428 x 510 mm
- 5 2100-sheet tray  
350 x 428 x 510 mm
- 6 Castor base  
126 x 521 x 693 mm

- 7 Staple, hole punch finisher  
263 x 462 x 507 mm
- 8 Staple finisher  
246 x 435 x 414 mm
- 9 Output expander  
165 x 421 x 380 mm
- 10 4-Bin letterbox  
272 x 421 x 384 mm
- 11 High capacity output expander  
310 x 421 x 335 mm
- 12 250-sheet tray  
80 x 428 x 510 mm

- 13 550-sheet lockable tray  
110 x 428 x 510 mm
- 14 250-sheet lockable tray  
80 x 428 x 510 mm
- 15 Swivel cabinet  
263 x 476 x 600 mm
- 16 Adjustable printer stand  
584.2 x 596.9 x 596.9
- 17 Spacer to add additional height  
110 x 428 x 510 mm

Standard  
 Optional

Note 1: Supports up to 4 optional trays. For maximum paper input capacity, instal 3 optional 550-sheet trays and one optional 2100-sheet tray. When a 2100-sheet tray is installed, it must be the bottom tray, and a castor base is required.

Note 2: Supports many output configurations, including: any combination of up to three output expanders and 4-bin letterboxes; OR staple finisher with 4-bin letterbox; OR staple finisher with output expander; OR output expander with high capacity output expander; OR the staple, hole punch finisher; OR any single output option by itself. When installing the optional stapler, it must always be on top. When installing the optional high capacity output expander, it must always be on the bottom.

Note 3: All measurements are shown as height x width x depth. For more information about supported configurations, refer to the Printer, Option and Stand Compatibility Guide at [http://www.lexmark.com/publications/furniture\\_safety/](http://www.lexmark.com/publications/furniture_safety/)

© 2018 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries. AirPrint® and the AirPrint Logo® are trademarks of Apple, Inc. ENERGY STAR® is a U.S. registered mark. Google Cloud Print™ is a trademark of Google, Inc. MOPRIA®, the Mopria® Logo™ and the Mopria® Alliance logos are trademarks, service marks, and certification marks of Mopria Alliance, Inc. in the United States and other countries. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (<http://www.openssl.org/>).

## Product specifications

## Lexmark MS823dn

### Print

|  |  |
|--|--|
| Display  | 2.4-inch (60 mm) Colour LCD display  |
| Print Speed: Up to <sup>6</sup>                | Black: 61 ppm  |
| Time to First Page: As fast as                 | Black: 4.2 seconds   |
| Print Resolution                               | Black: 1200 Image Quality, 1200 x 1200 dpi, 2400 Image Quality, 300 x 300 dpi, 600 x 600 dpi |
| Memory / Processor                             | Standard: 512 MB / Maximum: 4608 MB / Dual Core, 1000 MHz                                    |
| Hard Disk                                      | Option available   |
| Recommended Monthly Page Volume <sup>2</sup>   | 5000 - 75000 pages   |
| Maximum Monthly Duty Cycle: Up to <sup>3</sup> | 300000 pages per month   |

### Supplies<sup>7</sup>

|   |  |
|---|--|
| Laser Cartridge Yields (up to) <sup>1</sup>     | 7,500-page Cartridge, 15,000-page High Yield Cartridge, 35,000-page Extra High Yield Cartridge, 55,000-page Ultra High Yield Cartridge |
| Imaging Unit Estimated Yield: Up to             | 150000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage  |
| Cartridge(s) Shipping with Product <sup>1</sup> | 11,000-page Starter Return Program Toner Cartridge   |

### Paper Handling

|                              |  |
|------------------------------|--|
| Included Paper Handling      | 550-Sheet Input, 100-Sheet Multipurpose Feeder, 550-Sheet Output Bin, Integrated Duplex  |
| Optional Paper Handling      | 250-Sheet Tray, 550-Sheet Tray, 2100-Sheet Tray, 250-Sheet Lockable Tray, 550-Sheet Lockable Tray, 4-Bin Mailbox, Staple Finisher, Staple Punch Finisher, High Capacity Output Expander, Output Expander |
| Paper Input Capacity: Up to  | Standard: 650 pages 75 gsm bond / Maximum: 4400 pages 75 gsm bond  |
| Paper Output Capacity: Up to | Standard: 550 pages 75 gsm bond / Maximum: 2550 pages 75 gsm bond  |
| Media Types Supported        | Card Stock, Dual Web Labels, Envelopes, Integrated Labels, Paper Labels, Plain Paper, Transparencies, Refer to the Paper & Specialty Media Guide   |
| Media Sizes Supported        | 10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Oficio, A6  |

### General Information<sup>4</sup>

|   |   |
|---|---|
| Standard Ports                                | One Internal Card Slot, USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A) |
| Optional Network Ports / Optional Local Ports | Marknet N8370 WiFi Option, MarkNet N8230 Fiber Ethernet Print Server / Internal RS-232C serial, Internal 1284-B Bidirectional Parallel                                  |
| Noise Level: Operating                        | Print: 58 dBA   |
| Specified Operating Environment               | Humidity: 8 to 80% Relative Humidity, Temperature: 10 to 32°C (50 to 90°F), Altitude: 0 - 2896 Meters (9,500 Feet)  |
| Product Warranty                              | 1-Year Onsite Service, Next Business Day  |
| Size (mm - H x W x D) / Weight                | 445 x 428 x 510 mm / 25.4 kg  |

All information in this brochure is subject to change without notice. Lexmark is not liable for any errors or omissions.

**This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.**

<sup>1</sup>Average standard page yield value declared in accordance with ISO/IEC 19752. <sup>2</sup>"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. <sup>3</sup>"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. <sup>4</sup>Printers are sold subject to certain license/agreement conditions. See [www.lexmark.com/printerlicense](http://www.lexmark.com/printerlicense) for details. <sup>5</sup>Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity. <sup>6</sup>Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: [www.lexmark.com/ISOspeeds](http://www.lexmark.com/ISOspeeds). <sup>7</sup>Product functions only with replacement cartridges designed for use in a specific geographical region. See [www.lexmark.com/regions](http://www.lexmark.com/regions) for more details.