C911 / C931 Specifications





The C911 and C931 have been designed to meet the needs of the graphic arts and creative industries and is also well suited to general office applications, removing the need for two printers. Built to offer essential levels of high quality output, the C911 and C931 are robust and reliable, which are key requirements in these demanding markets.

Plus, the C931 is also fully compatible with an optional EFI Fiery XF 5.0 server which enables advanced colour management, including spot and process colours, optimising colour depth and print quality.

Stunning high definition colour

The C911 and C931 use digital LED technology and our Multi-Level ProQ technology to produce high definition printing in the sharpest and most vibrant print output available.

- Superb print resolution of 1200 x 1200dpi
- Multi-Level ProQ technology enhances colour print output
- Fully compatible with EFI Fiery® XF for advanced colour management (C931 only)

Lowest total cost of ownership

The C931 delivers significant cost savings against comparative printers, combining a highly competitive capital cost with ultra-high capacity toner cartridges.

- Highly competitive initial capital cost
- Reduced operating costs through ultra-high capacity toner cartridges (38K) and drums (40K)
- Separate toners and drums for reduced wastage
- Energy efficient for reduced energy usage
- Three year on-site warranty on registration of your product within 30 days of purchase^

Speed that you can rely upon

Highest printing speeds on the market with stunning high definition output that cannot be beaten.

- Time to first print less than 8 seconds
- A3 print speeds of 28ppm in colour/mono (up to 50ppm in colour/mono for A4)
- 2GB RAM and 1.2GHz processor for rapid throughput (1.0GHz processor for C911)

Media flexibility to beat all others

The C911 and C931 beat the competition hands down when it comes to media flexibility, printing a complete range of media in-house.

- Widest paper handling A6 to SRA3 and banner lengths up to 1.3m
- Print on paper stock up to 360gsm single sided and 320gsm duplex
- Use a wide range of media including gloss paper, film, transfer paper, waterproof paper and more
- 530 sheet tray as standard, up to 2,950 sheets with optional trays
- Robust 300 sheet multi-purpose tray for added flexibility
- Duplex printing as standard

A3/A4	~
Colour/Mono	~
Prints A6 to 1321mm, up to 360gsm	~
1 - 30+ usars	.4



C911 / C931 - Colour and Mono Printer

PRINTER			
Print speed	A4: 50ppm colour, 50ppm mono; A3: 28ppm colour, 28ppm mono		
Time to first print			
Warm up time	50 seconds or less from power on		
Processor speed	C911: 1.0GHz; C931: 1.2GHz		
INTERFACE AND SOFTWARE			
Connectivity	Hi-Speed USB 2.0, 10Base-T/100Base-TX/1000Base-T		
Printer languages	PCL5c, PCL6 (PCL XL), Adobe PostScript 3 with direct PDF Printing (v1.7), XPS, SIDM		
Network & protocols	All major network protocols supported via ethernet card with internal web server for printer and network card set-up and management. TCP/IP: IPv4/v6, ICMP, ICMPv6, IGMP, IGMPv2, LPR, Port9100, IPP, IPPS, FTP, FTP over SSL, HTTP, HTTPS, TELNET, IPP, Auto IP, LLTD, BOOTP, DHCP, SNMPv1/v3, SNMP Trap, DNS, DDNS, UPnP, Bonjour, WINS, SSL/TLS, SMTP, SMTP over SSL, POP3, SNTP, JCDP, FLDP, ODNSP, WSDPrint, WSD-Discovery, Web JetAdmin, NetBIOS over TCP, EtherTalk		
OS Compatibility ¹	Windows 7 (32-bit & 64-bit) / Windows 8 (32-bit & 64-bit) / Windows Vista (32-bit & 64-bit) / XP (32-bit & 64-bit) / Server 2003 (32-bit & 64-bit) / Server 2008 (32-bit & 64-bit) / Server 2008 R2 (64-bit) / Server 2012 (64-bit); Mac OS9 / OS X 10.3.9 - 10.9		
Advanced networking and security	IPv6, 802.1x authentication, SMTP Server Authentication, SMMPv3, SSL3/TLS encryption, HTTPS encryption, Protocol On/Off, Protocol Port No. Change, MAC filtering, IP filtering, IF sec, EAP-PEAP, EAP-TLS, Secure Erase³, Secure Print³, Secure Print Job Encryption³, Storage Devices entire Encryption³, Storage(HDD) Initialize (format)³		
Utility suite ¹	Print Job Accounting ² , Print Job Accounting Enterprise ² , Print Job Accounting Client, PrintSuperVision.net ² , Template Manager ² , Color Correct, Color Swatch ² , Configuration Tool, PS Gamma Adjuster, Profile Assistant (Mac Only), PDF Direct Print, EFI Fiery XF Server Option (External color management server, C931 only).		
Typefaces			
Printer fonts	87 scalable PCL fonts, Lineprinter/OCR-A/OCR-B/USPSZIP bitmap fonts, 10 TrueType fonts, 136 Adobe PostScript Type 1 fonts		
Barcode	UPC-A, UPC-E, EAN/JAN-8, EAN/JAN-13, Interleaved 2of5, Code39, Code128, EAN/UCC-128, CODABAR, ZIP+4 POSTNET: PDF417/QR code 2D barcodes		
PRINT QUALITY			
Resolution	ProQ2400 Multi-level technology, 1200 x 1200dpi		
Enhancements			
Paper handling			
Paper capacity	Tray 1: 530 sheets of 80gsm; Multi-purpose tray: 300 sheets of 80gsm		
Paper capacity optional trays	Tray 2: 530 sheets of 80gsm; Tray 3: 530 sheets of 80gsm; High Capacity Feeder: 1,590 sheets of 80gsm		
Maximum paper capacity	2,950 sheets of 80gsm		
Paper sizes	Tray 1/2/3: A3, SRA3 (up to 330 x 457mm), SRA4, A4, A5, A6, B4, B5, B6; Multi-purpose tray: A3, SRA3, SRA4, A4, A5, A6, B4, B5, B6 Custom size: Width 64 - 330mm Length 89 - 1,321mm; High Capacity Feeder: A3, SRA3 (up to 328 x 457mm), SRA4, A4, A5, A6, B4, B5, B6		
Paper weight	Tray 1/2/3: 52 to 320gsm; Multi-purpose tray: 52 to 360gsm; Duplex: 64 to 320gsm; High Capacity Feeder: 52 to 320gsm		
Duplex	Standard		
	(40 1 1 200 1 1		
Paper output	610 sheets face down tray, 300 sheets face up tray		

_				
റ	PFR	ATOR	PΔN	FI

Display 10.9cm Colour Graphic LCD (480x272 dots)

GENERAL FEATURES

GENERAL I EATORES		
Memory	Standard RAM: 2GB; Maximum RAM: 2GB	
	Optional Hard Disk Drive: 160GB	
Environment	Operating temperature/humidity: 10°C to 32°C (17°C to 27°C recommended) / 20% to 80% RH (50% to 70% RH recommended)	
	Storage temperature/ humidity: -10°C to 43°C, 10% to 90% RH	
Power supply	Single phase 230V AC +/-10%, frequency 50/60Hz +/- 2%	
Power consumption	Typical: 1100W; Max: 1600W; Idle: 40W (average); Power Save: <34W; Deep Sleep: <4W; Off Mode: <0.5W	
Noise level	Operating: 57dB(A); Standby: 34dB(A) or less; Power save: Inaudible	
Dimensions (HxWxD)	640 x 699 x 625mm	
Weight ⁴	97.6kg	
Duty cycle	Average: 25,000 pages/month; Maximum: 300,000 pages/month	
Warranty	3 years extended warranty upon registration within 30 days of purchase^	
Product order number	C911dn: 45530408; C931dn: 45530506	

ACCESSORIES (ORDER NUMBERS)

,		
2nd/3rd paper tray	45530703	
2nd/3rd paper tray with castor	45530903	
High Capacity Feeder	45530803	
Hard Disk Drive	160GB: 44622302	
FFI Fiery XF 5 0	45592303 (for use with C931 only)	

CONSUMABLES (ORDER NUMBERS)

,		
Toner cartridge* (38,000 pages)	Cyan: 45536519; Magenta: 45536518; Yellow: 45536517; Black: 45536520	
Toner cartridge* (24,000 pages)	Cyan: 45536431; Magenta: 45536430; Yellow: 45536429; Black: 45536432	
Image drums** (40,000 pages)		
Transfer Belt (150,000 pages)	45531213	
Fuser Unit (150,000 pages)	45531113	
Waste Toner Box (40,000 pages)	45531503	

^{*}Toner: Number of A4 pages @ ISO coverage. Printer shipped with toner for 10,000 pages @ ISO. **Drum: Average number of A4 pages printed.

¹Check local OKI website for latest driver releases and OS compatibility; ²Windows only; ³HDD required; ⁴Including all consumables

Consumables Information: For the protection of your printer, and in order to ensure that you benefit from its full functionality, this model has been designed to operate only with genuine OKI toner cartridges. These can be identified by the OKI trademark. Any other toner cartridge may not operate at all, even if it is described as "compatible", and if it does work, your printer's performance and print quality may be degraded.

Scan here



3 Year On-site Warranty²

Our devices are manufactured to the highest standards of quality and technology, which has been confirmed by independent tests. We are so convinced of the high quality of our products that we are offering you an extension of the standard warranty period to 3 years at no extra cost to you. Simply register your product within 30 days of purchase to be eligible for our unique all inclusive offer. Fully covered by OK!! For further information please visit: http://warranty.oki.com.au Without registration, the standard Australian 1 year warranty applies.



Level 1, 67 Epping Road Macquarie Park, NSW 2113 Australia

T 1800 800 140 F 02 8071 0010

www.oki.com.au



